CANARA BANK

INVITATION TO TENDER

ONLY FOR EMPANELLED CONTRACTORS

<u>OF</u>

CIRCLE OFFICE KOLKATA

TENDER FROM ANY OTHER CONTRACTOR WILL BE SUMMARILY REJECTED

INSTRUCTION TO BIDERS

AND

GENERAL CONDITIONS OF CONTRACT

FOR

FURNISHING WORKS

 \mathbf{AT}

CANARA BANK – KOLKATA PRINCE ANWAR SHAH ROAD BRANCH

TENDER NO.: 67/24-25/BDS

NAME OF THE CONTRACTOR:

ADDRESS:

NOTICE INVITING THE TENDER

То,		
M/s		
Sealed tenders on item rate basis are ifurnishing Works at premises of Kolkata Tender Documents may be obtained a Section, Circle Office Canara Bank 01.10.2024 till 09.10.2024.	Pri at f	ince Anwar Shah Road Branch . ree of cost from the Premises & Estate
Earnest Money Deposit	:	NIL
Period of completion	:	20 days
Last date, time and place for Submission of tender	:	On or before 3:00 pm, 09.10.2024 to The Assistant General Manager, General Administration Section Canara Bank, Circle Office Kolkata
Time and date of opening of tender	:	3.30 pm on 09.10.2024
The Bank will not be bound to accept to accept or reject any or all the whatsoever.		<u> </u>
		Assistant General Manager Premises & Estate Section Canara Bank, Circle Office Kolkata

Date: 01.10.2024

.....

GENERAL RULES & INSTRUCTIONS TO TENDERERS

Name of the work: Furnishing Works to be carried out at premises of Kolkata Prince Anwar Shah Road Branch

The rates quoted shall also be inclusive of materials, labour charges, work contract tax, surcharge and all the taxes except GST.

GST WILL BE PAID EXTRA.

The rates quoted by the tenderer shall hold good till the completion of the work from the date of issue of the "WORK ORDER" and no enhancement in the rates are allowed during the period of execution of the work under any circumstances. The rates quoted shall also cover for the work to be executed before and after office hours and also on holidays.

The time stipulated for the completion of the work is 20 days from the date of issue of the WORK ORDER and the work is to be carried out as per the convenience of occupants without disturbing other occupants of the building.

TENDERS:

The entire set of tender paper issued to the tenderer should be submitted fully priced and also signed on the last page together with initials on every page. Initials / signatures will indicate the acceptance of tender papers by the tenderers.

The schedule of quantities shall be filled in as follows:

- o The "rate" column to be legibly filled in ink in both English figures and words.
- o 'Amount' column to be filled in for each item and the amount for each sub-head as detailed in the "schedule of quantities".
- All corrections to be initialed.
- The "Rate" column for all the items shall be filled up.
- The "Amount" column for the items for which the quantities are not mentioned shall not be filled up.
- In case of any errors / omissions in the quoted rates, the rates mentioned in the tender in words shall be taken as correct rates.

No modifications, over-writings or corrections can be made in the tender papers by the tenderer, but may at his option offer his comment or modifications in a separate sheet of paper attached to the original tender papers.

The Bank reserves the right to reject the lowest or any tender or all of the tenders for each section or to split up and distribute any item of work to any specialist firm or firms, without assigning any reason.

The tenderers should note that tender is strictly on the item rate basis and their attention is drawn to the fact that the rates for each and every item should be correct, workable and self – supporting. If called upon by the bank, detailed analysis of any or all the rates shall be submitted. The architects/bank shall not be bound to accept the contractor's analysis.

The Quantity mentioned in the BOQ is approximate measurements. The works will be paid for as "measured work" on the basis of actual work done and not as "lump sum" contract.

All the items of work described in the schedule of quantities are to be deemed and paid as complete works in all respects and details including preparatory and finishing works involved, directly, related to and reasonably detectable from the drawings, specifications and schedule of quantities and no further extra charges will be allowed in this connection. In the case of lumpsum charges in the tender in respect of an item of works, the payment of such items of work will be made for the actual work done on the basis of lump-sum charges as assessed to be payable by the architects/bank.

The bank has power to add or delete any work or described in specifications or included in schedule of quantities and intimates the same in writing but no addition, omissions or variation shall be made by the contractor without authorization from the bank. No variation shall vitiate the contract. The bank reserves the right to delete any of the items in the tender without assigning any reasons whatsoever.

The tenderer shall note that his tender shall remain open for consideration for a period of 90 days from the date of opening of tender.

AGREEMENT

The successful contractor is required to sign agreement as may be drawn up to suit the local conditions and shall pay for all the stamps and legal expenses incidental thereto. The original will be kept with the Bank and duplicate with contractor.

EARNEST MONEY AND SECURITY DEPOSIT:

There is NO Earnest Money Required to deposit/ submit along with the bids. Retention Money shall be deducted from the final bill at 5% of the gross value of bill. The Retention amount will be refunded to the contractor 15 days after the end of defects liability period provided he has satisfactorily carried out all the work and attended to the entire defect in accordance with the condition of the contract. No interest is allowed on Retention Money.

A part of the Security Deposit if and as decided by the constituent bank can also be furnished in the form of a Bank Guarantee on the bank other than that of the constituent bank.

CONTRACTOR TO PROVIDE EVERYTHING NECESSARY:

The contractor shall provide everything necessary for the proper execution of the work according to the intent and meaning of the drawings, schedule of the quantities and specifications taken together weather the same may or may not be particularly shown or described therein provided that the same can reasonably be inferred there from and if the contractor finds any discrepancies therein he shall immediately and in writing, refer the same to the Architects/Bank whose decision shall be final and binding.

The rates quoted against individual items will be inclusive of everything necessary to complete the said items of works within the contemplation of the contract, and beyond the unit price. No extra payments will be allowed for incidental or contingent labour and/or materials inclusive of all taxes and duties whatsoever except for specific items, if any, stipulated in tender documents

The contractor shall supply, fix and maintain at his own cost, for the execution of any work, all tools, tackles, machineries and equipment and all necessary scaffolding, staging and lighting by night as well as by day required not only for proper execution and protection of the said work.

The contractor shall take down and remove any or all such scaffoldings as occasion shall be required or when ordered to do so, and shall fully reinstate and make good all matters and things disturbed during the execution of work to the satisfaction of architect/bank.

The contractor shall all times give access to workers employed by the bank or any men employed at site and to provide such parties with proper sufficient and if required, special scaffolding and ladder and provide them lighting as may be required to enable such workmen to inspect the work, lay or fix pipes, Civil & furnishing wiring, special fittings etc. The quoted rates of tenderers shall accordingly include all these above-mentioned contingent works.

LIQUIDATED DAMAGES:

Should the work be not completed to the satisfaction of bank within the stipulated period, the contractor shall be bound pay the bank a sum calculated as given below by way of Liquidated Damages after the expiry of completion date

.1.00% of the estimated amount shown in the tender per week subject to a ceiling of 10% of the accepted contract sum.

TIME PERIOD FOR COMPLETION: 20 days from the date of award of work.

FINAL PAYMENTS

The final bill shall be accompanied by a certificate of completion from the Occupant/Bank Officials. Payments of the final bill shall be made after deduction of retention money as specified in clause 9 of these conditions which sums shall be refunded after the completion of the defects liability period after receiving the banks certificate that the contractor has rectified all defects to the satisfaction of the banks. The acceptance of payments of the final bill by the contractor would indicate that he would have no further claims in respect of the work executed.

ESCALATION:

The rates quoted shall be firm throughout the tenure of the contract [including extension of time, if any granted] and will not be subject to any fluctuation due to increase in cost of materials, labour, sales tax, octroietc, unless specifically provided in these documents.

CONTRACTORS EMPLOYEES:

The contractor shall employ technically qualify and competent supervisors for the work who shall be available [by turn] throughout the working hours to receive and comply with the instructions of the bank officials. The contractor shall engage at least one experienced engineer, as site in-charge for the execution of the work the contractor shall employ in connection with the work persons having appropriate skill or ability to perform their job efficiently. The contractor shall employ local labours on the work as far as possible. No laborers below age of 16 and who is not an Indian national shall be employed on the work. Any laborers supplied by the contractor to be engaged on the work on day-work basis either wholly or partly under the direct order or control of bank or its representative shall be deemed to a person employed by the contractor.

The contractor shall comply with provision of all labour legislation including the requirements of

- a. Payments of minimum wages act
- b. Employers liabilities
- c. Workmen's compensation act
- d. Contract labour (regulation and abolition) act, 1970 and central rules 1971
- e. Apprentices act 1961
- f. Any other act or enactment relating thereto and rules framed there under from time to time

The contractor shall keep the bank saved harmless and indemnified against claims if any of the workmen and all costs and expenses as may be incurred by the bank in connection with any claim that may be made by any workmen.

The contractor shall comply at his own cost with the order of requirement of any health officer of state or any local authority or of the bank regarding the maintenance of proper environmental sanitary condition of the area.

The contractor shall arrange to provide first aid treatment to the laborers engaged on the works. He shall within 24 hrs of occurrence of any accident at or about the site or in connection with execution of work, report such accidents to the bank and also the competent authority where such report is required by law.

The contractor shall obtain all Risk Insurance Policy at their cost within 7 days of commencement of work, for the laborers/workmen working at the site including the work till the work is completed. The policy shall be in the joint name of the Bank and contractor and Bank's name shall appear First.

PAYMENTS:

The contractor, in the form prescribed by the bank shall prepare all the bills and submit the same to Bank with measurement of work. Normally one interim bill shall be prepared each month. Bank may release payment within 15 days of receipt of bills/after check measurement, after deduction of retention money, Income Tax etc.The contractor shall have a competent engineer at site for the supervision of the work.

The contractor shall have to make his own arrangements for watch and ward of the work/building, till the work is handed over to the bank.

The decision of the bank will be final and binding with regard to the quality of work is concerned.

The contractor is responsible for procuring the required materials for the work and stores the same at site at his cost and risk.

The amount stated in the interim certificate shall be the 75% of total value of the work executed up to date of the bill, less the amount to be retained by the bank as retention money. If the bank has supplied any materials or goods to the contractors, the cost of such materials will be progressively deducted from the amount due to the contractor on accordance with the quantities consumed in the work. All the interim payments shall be regarded as payments by way of advance against the final payment only and not as payments for works actually done and completed and shall not preclude the requiring of bad, unsound or imperfect or unskilled work to be removed and taken away and reconstructed or re-erected or be considered as an admission of the due performance of the contract or any part there of if any respect or accruing of any claim nor shall it conclude, determine of effect in any way the power if the bank under conditions or any of them add to the final settlement and adjustment of the accounts or otherwise or in any other way or affect the contract.

The contractor shall submit the final bill within one month from the date of completion of the work. A certificate of completion from the bank shall accompany the final bill. The payment of the final bill shall be made after deduction of retention money as specified elsewhere in these documents.

ARBITRATION:

All disputes or differences of any kind whatsoever which shall at any time arise between the parties here to touching or concerning the works or the execution or maintenance thereof of this contract or the rights touching or concerning the works or the execution of maintenance thereof of this contractor or the construction remaining operation or effect thereof or to the rights or liabilities of the parties are arising out of or in relation thereto whether during or after determination foreclosure or branch of the contract[other than those in respect of which the decision of any person is by the contract expressed to be final and binding] shall after written notice by either party to the contract to the other of them and to the employer hereinafter mention to deal referred for adjudication to a sour arbitrator to be appointed as hereinafter provided.

For the purpose of appointing the sole arbitrator referred to above, the employer will send within 30 days of receipt of the notice, to the contractor a panel of 3 names of persons who shall be presently unconnected with the organization for which the work is executed.

The contractor shall on receipt of the names as aforesaid, select, anyone of the person's name to be appointed as a sole arbitrator and communicate his name to the employer within 30 days of the receipt of the names. The employer shall thereupon without any delay appoint the person as the sole arbitrator. If the contractor fails to communicate such selection as provided above within the period specified, the competent authority shall make the selection and appoint the selected person as the sole arbitrator.

If the employer fails to send to the contractor the panel of 3 names as a foresaid within the period specified, the contractor shall send to the employer a panel of 3 names of persons who shall be unconnected with either party. The employer shall on receipt of the name as a foresaid select anyone of the person's names and appoint him sole arbitrator. If the employer fails to select the person and appoint him as a sole arbitrator within 30 days of the receipt of the panel and inform the contractor accordingly, the contractor shall be entitled to appoint one of the persons from the panel as the sole arbitrator and communicate his name to the employer.

If the arbitrator as appointed is unable or unwilling to act or resigns his appointment or vacates his office due to any reason whatsoever another sole arbitrator shall be appointed as aforesaid.

The work under contract shall, however, continue during arbitration proceedings and payment due or payable to the contractor shall be withheld on account of such proceedings.

PAGE No. 7

The arbitrator shall be deemed to have entered on the reference the data he issued notice to both the parties fixing the date of the first hearing.

The arbitrator may from time to time, with the consent of parties, enlarge the time or making and publishing the award.

The arbitrator shall give a separate award of each disputes or difference referred to him. The arbitrator shall decide each dispute in accordance with the terms of the contract and give a reasonable award. The venue of arbitration shall be such place as may be fixed by the arbitrator in his sole discretion.

The fee, if any, of the arbitrator shall, if required to be paid before the award is made and published, be half and half by each of the parties. The cost of the reference and of the award including the fees, if any, of the arbitrator who may direct to and by whom and in what manner, such costs or any part thereof shall be paid and may fix or settle the amount of costs to be so paid.

The award of the arbitrator shall be final and binding on both the parties.

Subject to aforesaid the provision of the arbitration act 1940 or any statutory modification or reenactment thereof and the rules made there under, and for the time being in force, shall apply to the arbitration proceeding under this clause.

The employer and the contractor hereby also agree that arbitration under the clause shall be a condition precedent to action under the contract with regard to the matters hereby expressly agreed to be so referred to arbitration.

Date:	Signature of the Contractor
	With seal and address

IEDULE OF FURNISHING WORKS- KOLKATA PR				1
DESCRIPTION	QNTY.	UNIT	RATE	AMOUNT
			RS.	RS.
FRONT & SIDE PARTITIONS				
Supplying and erecting low height				
opaque partitions (from 1'-6"- 4FT/5FT				
high)				
as per drawing and conforming to the following specifications:				
	+			
·				
• •	+			
	+			
. •				
•				
. • •				
•				
·				
•				
-				
	100	saft.		
	. 30	- H		
and the second processing				
FULL HEIGHT PARTLY GLAZED				
WOODEN PARTITIONS in BM's ROOM				
• • • • • • • • • • • • • • • • • • • •				
<u></u>				
wood preservatives, 50mm				
	LOW HEIGHT SOLID/PARTLY GLAZED WOODEN PARTITIONS IN COUNTER FRONT & SIDE PARTITIONS Supplying and erecting low height opaque partitions (from 1'-6"- 4FT/5FT high) as per drawing and conforming to the following specifications: Basic Framework: Well seasoned Malayasian sal wood sections, treated with two coats of wood preservatives, 50mm x 50mm (minimum) at maximum 600 mm horizontal or vertical spacing as per site conditions. Vertical Members shall be suitably anchored and at ceiling level to ensure rigidity. Skin Membrane: 6 mm thick BWR grade plywood on each face with 4 mm grooves formed as per drawings/instructions. Finishing: 1.0mm thick laminate sheet of combination shades as per instructions on both sides. Quoted rates shall include all necessary materials, accessories and also allow provisions for electrical/telephone/computer wiring conduits and switch boxes, etc (Materials of wiring conduits and switch boxes shall be separately paid for.) FULL HEIGHT PARTLY GLAZED WOODEN PARTITIONS in BM's ROOM & UPS RM Supplying and erecting full height partlyglazed partition (varying from 8'6" to 10ft high) as per drawing and conforming to the following specifications: Basic Framework: Well seasoned Malayasian sal wood sections, treated with two coats of	DESCRIPTION LOW HEIGHT SOLID/PARTLY GLAZED WOODEN PARTITIONS IN COUNTER FRONT & SIDE PARTITIONS Supplying and erecting low height opaque partitions (from 1'-6"- 4FT/5FT high) as per drawing and conforming to the following specifications: Basic Framework: Well seasoned Malayasian sal wood sections, treated with two coats of wood preservatives, 50mm x 50mm (minimum) at maximum 600 mm horizontal or vertical spacing as per site conditions. Vertical Members shall be suitably anchored and at ceiling level to ensure rigidity. Skin Membrane: 6 mm thick BWR grade plywood on each face with 4 mm grooves formed as per drawings/instructions. Finishing: 1.0mm thick laminate sheet of combination shades as per instructions on both sides. Quoted rates shall include all necessary materials, accessories and also allow provisions for electrical/telephone/computer wiring conduits and switch boxes, etc (Materials of wiring conduits and switch boxes shall be separately paid for.) FULL HEIGHT PARTLY GLAZED WOODEN PARTITIONS in BM's ROOM & UPS RM Supplying and erecting full height partlyglazed partition (varying from 8'6" to 10ft high) as per drawing and conforming to the following specifications: Basic Framework: Well seasoned Malayasian sal wood sections, treated with two coats of	LOW HEIGHT SOLID/PARTLY GLAZED WOODEN PARTITIONS IN COUNTER FRONT & SIDE PARTITIONS Supplying and erecting low height opaque partitions (from 1'-6"- 4FT/5FT high) as per drawing and conforming to the following specifications: Basic Framework: Well seasoned Malayasian sal wood sections, treated with two coats of wood preservatives, 50mm x 50mm (minimum) at maximum 600 mm horizontal or vertical spacing as per site conditions. Vertical Members shall be suitably anchored and at ceiling level to ensure rigidity. Skin Membrane: 6 mm thick BWR grade plywood on each face with 4 mm grooves formed as per drawings/instructions. Finishing: 1.0mm thick laminate sheet of combination shades as per instructions on both sides. Quoted rates shall include all necessary materials, accessories and also allow provisions for electrical/telephone/computer wiring conduits and switch boxes, etc (Materials of wiring conduits and switch boxes shall be separately paid for.) FULL HEIGHT PARTLY GLAZED WOODEN PARTITIONS in BM's ROOM & UPS RM Supplying and erecting full height partlyglazed partition (varying from 8'6" to 10ft high) as per drawing and conforming to the following specifications: Basic Framework: Well seasoned Malayasian sal wood sections, treated with two coats of	DESCRIPTION CONTY. DESCRIPTION LOW HEIGHT SOLID/PARTLY GLAZED WOODEN PARTITIONS IN COUNTER FRONT & SIDE PARTITIONS Supplying and erecting low height opaque partitions (from 1'-6"- 4FT/5FT high) as per drawing and conforming to the following specifications: Basic Framework : Well seasoned Malayasian sal wood sections, freated with two coats of wood preservatives, 50mm x 50mm (minimum) at maximum 600 mm horizontal or vertical spacing as per site conditions.Vertical Members shall be suitably anchored and at ceiling level to ensure rigidity. Skin Membrane : 6 mm thick BWR grade plywood on each face with 4 mm grooves formed as per drawings/instructions. Finishing : 1.0mm thick laminate sheet of combination shades as per instructions on both sides. Quoted rates shall include all necessary materials, accessories and also allow provisions for electrical/telephone/computer wiring conduits and switch boxes, etc (Materials of wiring conduits and switch boxes shall be separately paid for.) FULL HEIGHT PARTLY GLAZED WOODEN PARTITIONS in BM's ROOM & UPS RM Supplying and erecting full height partlyglazed partition (varying from 8 '6" to 10ft high) as per drawing and conforming to the following specifications: Basic Framework : Well seasoned Malayasian sal wood sections, treated with two coats of

	x 50mm (minimum) at maximum 600 mm horizontal or			
	vertical spacing as per site			
	conditions.			
	<u>Skin Membrane</u> : (Opaque portion			
	upto 900mm from floor			
	level with 1x6 mm thick BWR grade			
	plywood on each face			
	with 4x4mm grooves formed at the			
	top layer as per drawings/instructions.			
	Glazing: 8mm thick clear float glass			
	fixed with continious			
	White or Steam Beech wood glazing			
	beads of approved shape			
	(finished 35x25 mm) all around,			
	polished & coated with NC			
	lacquer finish. The rate should also			
	include cost of decorative			
	etching on one side of the glass. Finishing: 1.0mm thick laminate			
	sheet of same or combination			
	shades			
	on both sides as per instructions.			
	Edge Moulds : All free top/end			
	surfaces shall have polished			
	white or steam beech wood moulds			
	of apprived shape (from			
	80x 25mm sections) with LC lacquer			
	in mat finish.			
	Skirting: 100mm high x 12 mm thick polished white or steam			
	beech wood skirting on both faces			
	with NC lacquer in Matt			
	finish.			
	Quoted rates shall include all			
	necessary materials, accessories			
	and also allow provisions for			
	electrical/telephone/computer			
	wiring conduits and switch boxes, etc (Materials of wiring			
	conduits and switch boxes shall be	185	Sq.Ft.	
	separately paid for.)	100	04	
			_	
3	FULL HEIGHT SOLID PARTITION WITH			
	BOTH SIDE LAMINATE			
	Supplying and erecting full height			
	opaque partitions (from 8'-6"			
	10ft. high) as per drawing and			
	conforming to the following			

T	specifications:			
	specifications:			
	Basic Framework : Well seasoned			
	Malayasian sal wood			
	sections, treated with two coats of			
	wood preservatives, 50mm			
	x 50mm (minimum) at maximum			
	600 mm horizontal or			
	vertical spacing as per site			
	conditions.Vertical Members shall			
	be suitably anchored and at ceiling			
	level to ensure rigidity.			
	<u>Skin Membrane</u> : 6 mm thick BWR			
	grade plywood on each			
	face with 4 mm grooves formed as			
	per drawings/instructions.			
	Finishing: 1.0mm thick laminate			
	sheet of combination shades as per			
	instructions on both sides.			
	Skirting: 100mm high plywood			
	skirting finished in 1mm thk.			
	Laminate			
	of combination shades as per			
	instruction and drawing.			
	Quoted rates shall include all			
	necessary materials, accessories			
	and also allow provisions for			
	electrical/telephone/computer			
	wiring conduits and switch boxes,			
	etc (Materials of wiring	400		
	conduits and switch boxes shall be	400	sqft.	
	separately paid for.)			
4	WORKSTATIONS			
	Providing, fixing and fitting in position			
	free standing work station			
	made of 19 mm thk. BWP Ply + 1.0			
	mm. Laminate of			
	approved make and colour for the			
	table top, sides & front apron			
	The table is supported on the left			
	side by a 1'-6" wide &			
	2'-0" deep drawer unit consisting of a			
	tea tray, one drawer			
	& a shuttered cabinet all in 1.0 mm			
	thk. laminate finish and Ply partition			
	on the right side . The table is			
	provided with a readymade metallic			
	CPU			
	Holder with swivel facility, (CPU HL			
	SW / INNOFITT systems or similar)			

	& readymade key board drawer of			
	engineering Plastics (KD 575 P MT/			
	INNOFIT System or similar) shall be			
	suspended below the table top.			
	Quoted rates shall also include cost			
	of polished white or steam beech			
	wood			
	moulding (finished 40x20 mm			
	section) to edges of table top;			
	polished			
	white or steam beech wood lipping			
	(6mm thick) to free edges of block			
	board/ plywood surfaces; approved			
	drawer - slides, concealed type			
	auto-closing shutter hinges and locks with keys in duplicate; other			
	necessary hardware and accessories including satin finish S.S.			
	handles,			
	knobs and wire - managers etc. of			
	approved quality & the table top			
	is finished with 5mm thick glass.			
A)	Approx. size of 1800 x900 x 750 mm	1	No.	
B)	Approx. size of 1500 x 750 x 750 mm	5	No.	
	A Proposition of the Article IIIII			
5	Providing, fitting & fixing the Cash			
	counters & Cabin			
	along with partitions all			
	complete:Internal Size of the			
	cash cabin :5'-0" (w) x 7'-0"(l) x 7'-			
	0"(h)			
5A	Providing fixing & fixing 2'-6" wide &			
	2'-6" high staff working top			
	made of 18mm thick BWP block			
	board of approved make			
	finished with 1.0 mm laminate of			
	approved make & shade.			
	The customer transaction top shall			
	be 1'-6" wide projecting 6"			
	on the customer side at a height of 1'			
	above the staff working			
	counter thus making a total height of			
	3'-6". The customer top is			
	made of 3/4" thk.Granite top(Black			
	galaxy) placed on 18mm thick BWP			
	blockboard which is cut & shaped			
	with edges round polished.			
	Below the working top/counter will			
	be 1'-4" wide drawer			

	cum shuttered cabinet unit on one			
	side & metallic CPU trolley on the other side with key board tray			
	with slide channels &			
	foot rest in between for each of the			
	cash counters specs same as			
	Banking			
	Counters. All the specification of the			
	drawer unit/CPU			
	trolley is same as that of Work station			
	in item no 6.			
	Below the Transaction top the portion			
	which is overlapping with			
	the working counter of 10" deep will			
	be covered by 2 sets of sliding shutters with a intermediate			
	shelf with			
	all locking arrangement for keeping			
	currency notes.			
	Both the staff working top & the			
	transaction top is rested &			
	supported together by a front Apron			
	or Double skin partition			
	which is similar in design and			
	specification as that of Banking			
	counters.			
	There will be neccesary grooves			
	between the two different			
	decorative laminates as shown in			
	the detail drawing & as directed. The counter will be			
	provided with wire manager.			
	The front portion of cash cage			
	above the transaction top			
	(from 3'-6" to 7'-0" height) will be			
	provided with 2 nos. of 12			
	mm thick float glass leaving a gap			
	of 2" between the two			
	glass panes so as to allow			
	conversation between the			
	customer & the cashier & a cut out of			
	8" x 4" at the central		D	
	bottom part of each of the	5	Rft.	
	transaction top.			
5B	Cash Cage Side, Intermediate & rear			
	Partitions with door			
	The intermediate/side/rear partition			
	with doors between			
	Cash Cabins as Partly glazed			

	Wooden Partition unto 7' 0" haight	
+	Wooden Partition upto 7'-0" height	
-	with the following specification:	
	<u>Basic Framework :</u> Well seasoned Malayasian sal wood	
+	sections, treated with two coats of	
	wood preservatives, 50 mm	
+	x 50mm (minimum) at maximum	
	600 mm horizontal or	
+	vertical spacing as per site	
	conditions. Vertical Members shall	
+	be suitably anchored at floor level to	
	ensure rigidity.	
	Exposed frame members in the	
	glazed portions shall have	
	wider spacing (approx. 1800 mm	
	clear) as per instructions.	
	Exposed members shall be finished	
	with 1.0mm thick laminate	
+	sheet of same or combination	
	shades, over 6 mm BWR grade	
+	plywood including 4 mm grooves at	
	locations as per instruction.	
	Skin Membrane : (Opaque portion	
	upto 1050 mm(3'-6") from floor	
	level with 6 mm thick BWR grade	
	plywood on each face	
	with 4x4mm grooves formed as per	
	drawings/ instructions.	
	Finishing : 1.0mm thick laminate	
	sheet of combination shades	
	as per instruction and drawing.	
5B	Skirting: 100mm high plywood	
	skirting finished in 1mm thk.	
	Laminate	
+	of combination shades as per	
	instruction and drawing.	
	Glazing: Strips of 8 mm thick clear	
	float glass fixed with continious	
	White or Steam Beech wood glazing	
	beads of approved shape	
	(finished 35x25 mm) all around,	
	polished & coated with NC lacquer	
	finish.	
	The rate should also include cost of	
	decorative etching on one side of	
	the	
	glass.	
	Quoted rates shall include all	
	necessary materials, accessories	
	and also allow provisions for	

					, ,
	electrical/telephone/computer				
	wiring				
	conduits and switch boxes, etc (
	Materials of wiring conduits and				
	switch				
	boxes shall be separately paid for.)				
	All exposed edges of the BWP ply &				
	blockboard are to be finished with				
	12 mm thk. Rubber wood lipping				
	which are to be polished as				
	directed.				
	Provision for extra wooden frame				
	work of same section				
	for intermediate glazing to be				
	included in the rate.				
	There will be provision for small				
	trays/windows for transfering				
	of small copy either from the				
	banking area to the cash cabins				
	or between the cash cabins as				
	directed by the architect.				
	The cost of all fittings of the door				
	:handle locks,aldrop handles,				
	hydraulic				
	door closer, night latch all of				
	appoved make of the doors				
	wherever required in the cash	135	SQFT.		
	section to be included.				
6	SIDE CREDENZO				
	consisting of a top row of two sets of				
	4" high drawers with				
	cabinets below with sliding shutters,				
	made of 19mm thick				
	BWR grade block boards all finished				
	in 1.0mm thk.laminate.				
	Exposed block board surfaces shall				
	be finished with 1.00mm				
	laminate sheet of approved shade				
	and make. Inner faces of				
	sliding shutters shall be polished in				
	approved color.				
	Free edges of block board shall				
	have polished white or steam				
	beech wood half round moulds (out				
	of 20 x 20 mm sections).				
	Inner faces of cabinet units shall be				
	polished in approved shade				
	quoted rates shall include cost of				
	necessary hardware , Viz				
				L	L

	handles, locks with keys in duplicate, etc.	6	Nos.	
7	P/F/F Full height /Low height filing cabinet/Over head Cabinet 1'-6"			
	deep			
	made of 18mm BWP blockboard with intermediate shelves.The			
	back of the cabinet to be made of 6mm thk.BWP ply fixed on the wall.			
	There will be one horizontal division and vertical dividers of same block board			
	at approx. 3ft.apart with sliding shutters for Low height & overhead cabinet.			
	All exposed surfaces & the shutters are finished with 1.0 mm thk.			
	decorative laminate of approved make & shade. Cost of all fittings			
	like brass hinges, godrej locks,magnetic hinges, godrej locks,			
	magnetic catches, steel matt finish "D" type handles shall be inclusive.			
Α	LOW HEIGHT CABINET	60	Sqft	
8	FLUSH DOOR			
	Supplying and fixing in position overall 37mm thick solid core hot pressed			
	phenol formaldehyde bonded approved flush door shutter finished			
	door shutter finished with 1.0mm thick laminate sheet of approved			
	shade and quality on both sides of the door shutter including cost of			
	hardware fittings e.g. mortice locks, brass hinges, hydrulic door closer,			
	door handles etc. of approved make and quality.			
а	Average size of shutter (D1): 3' 0"x 7'-0"	5	No.	
b	Average size of shutter (D2) : 2' 6"x 7'-0"(Pantry /Toilet Doors)	3	No.	
С	Swing Door : 3'(w) x 4' (h)	1	No.	
9	GLAZED DOOR SHUTTER			
9A	Providing, fixing & fitting in position Partly Glazed Door shutters made of			

		1		1
	specification similar to that of item			
	(8) hinged on 3 nos. brass hinges as			
	required			
	with the exception that the wooden			
	frame is of section 2" x 1.5". The cost			
	of all			
	fittings:handle locks, aldrop handles			
	door closer, night latch all of			
	appoved			
	make to be included.The glazed			
	_			
	portion will be between			
	3'-0" to 6'-8" of 6 mm thk. glasspanes			
	of approved quality.			
	Average size of shutter (D3): 3'-0"x	2	Nos.	
	7'-0" (Branch Head's Cabin & UPS			
	BATTERY RM)			
9B	MAIN ENTRANCE DOOR FOR			
	BRANCH & ATM			
	Providing & fixing in position Full glass			
	3'-6" wide Single leaf door cum			
	fixed glazing . The door shutter &			
	fixed glazing is made of 12mm thk.			
	SGG			
	impact resistance glass (toughened			
	glass) with pencil polish edges all			
	around.			
	Etching design for glass door as per			
	design.			
	Door & fixed glazing shall be fixed			
	with PATCH FITTING assembly			
	inclusive			
	of top and bottom patches, Floor			
	spring, Bottom lock, SS brushed			
	handle			
	of 2'0" long 1"dia on both sides.			
1	Glazed Door Shutters	75	° C C T	
		75	SQFT.	
2	Glazed Fixed partition	45	SQFT.	
10	Door Frames:			
	P/F/F Door frames made out of 4" x	0.30	CUMT	
	3" /3" x 1.5" clear Steam Beech wood			
	free of knots and proper rebates			
	and grooves be made before fixing			
	to the wall & finished with melamine			
	polish with necessary approved M.S			
	holdfast with split ends fixed with			
	G.S.screws including grouting with			

	1:2:4 concrete in brick work and/or with rawl plug in RCC construction and/or properly screwed and fixed in Partition as directed etc complete.			
11	PIN-UP NOTICE BOARD			
	Providing, fitting in position pin-up			
	board made of soft			
	cork board finished with the fabric as			
	approved,matching			
	with the colour scheme of the			
	banking hall with a R.W.			
	moulding all around the edges.	20	Sqft.	
12	PANELLING ON THE WALLS WITH LAMINATE FINISH OF PILLARS OF BRANCH Wall Panelling / column encasing (
	upto False ceiling height) works			
	as per Branch Ambience			
	Standardised manual of the Bank			
	conforming to the following			
	specifications :			
	Shall be made up of 2"x1" salwood framework with 12mm thk ply back up.			
	The framing shall be fixed at intervals of 2'0" c/c horizontally and vertically.			
	Shall be made up of 19mm thk			
	plywood as per site conditions.			
	The framing shall be fixed with 6mm			
	thick ply to form 4mm grooves			
	finished with 1mm thick approved color laminate of approved make at every			
	1ft interval.The skirting shall be finished with 3" wide 1.00mm approved			
	bi color laminate of approved make.			
	Quoted rates shall include all necessary materials, accessories and labour			
	and also allow provisions for electrical/telephone/computer wiring conduits &			
	switch boxes etc. complete with necessary jacking /thickening of			

	panels				
	to accommodate conduits/ switch				
	boxes.(Materials for wiring conduits				
	and				
	switch boxes shall be separately		Sqft.		
	paid for).	200	oq		
	para resp.				
10	A CD DANIELLING ON THE ATM WALLS				
13	ACP PANELLING ON THE ATM WALLS				
	Providing & erecting PANELLING		Sqft.		
	made out of 50mm x 38 mm x	250			
	1.2 mm hollow				
	aluminum square tube placed				
	600mm c/c both vertically and				
	horizontally finished with				
	3mm thk. ACP Sheets are fixed to				
	the Frame in 2ft panels with 3M or				
	equivalent ""				
	epoxy(neutral/black silicone)				
	Adhesive & mirror screws.				
	The Joints are to finished with silicon				
	based sealants. (Make: Aludecor, Alubond or				
	equivalent ISO certified brands).				
	Shade to be as per Bank's approval.				
	Measurement of height shall be				
	taken from F.L up to the False ceiling				
	underneath.				
	Rate should include the provision for				
	supporting the panelling from the				
	main ceiling.				
	Quoted rates shall include all				
	necessary materials, accessories				
	and labour				
	and also allow provisions for				
	electrical/telephone/computer				
	wiring conduits &				
	switch boxes etc. complete with				
	necessary jacking /thickening of				
	panels				
	to accommodate conduits/ switch				
	boxes.(Materials for wiring conduits				
	and				
	switch boxes shall be separately paid for).				
	to accommodate conduits/ switch				
	boxes.(Materials for wiring conduits				
	and				
	switch boxes shall be separately			+	
	paid for).				
	P = . = . 7.			1	1

14	TRAP DOOR & BOXING FOR ROLLING			
	SHUTTERS & COLLAPSIBLE GATE			
	WITH ACP FINISH FOR BRANCH & ATM			
	Providing and fixing trap doors			
	consisting of 1/4" thk. Marine ply			
	shutters with a clear opening of 4.5" opening for smooth operation			
	of shutters and rest is closed with			
	mirror screws (for opening for			
	servicing).			
	The shutters shall be finished with			
	approved ACP finish with all			
	materials			
	and frame of 2"x1 ½" teak wood sections shall be provided for			
	proper support and strength. Rate	200	SQFT	
	shall be inclusive of necessary	200	5 4.1	
	fittings like hinges(hafele/ebco			
	make), ball catches, tower bolts,			
	etc.			
15	WOODEN SHUTTERS WITH FRAME FOR			
	ELECTRICAL PANELS Providing and fixing 18mm thk. Com	40	SQFT	
	ply shutters with same ply frame.	40	30(1)	
	Division of shutters shall be made			
	equally according to the length.			
	Shutters shall be hinged to the			
	framework and finished with 1.0mm			
	thk. Laminate of approved colour			
	and shade on outer side and inside finised with 2 coats of enamel paint			
	of app colour and shade. Rate shall			
	be inclusive of all necessary			
	approved fittings like hinges, ball			
	catch,150 mm long SS Brush Finish			
	handle, tower bolts, locks, Aluminium			
	powder coated air vent grills and			
	necessary hardware fitings complete, etc.			
	complete, etc.			
16	Writing Ledge FOR BRANCH & ATM	2	NOS.	
	Providing & fixing Writing ledge of	_		
	size 750mm x 500 mm x 150mm with			
	pigeon hole type box below the top			
	made out of 19mm block board			
	finished with 1mm laminate fixed/ mounted on the wall with Angle			
	mounted on the wall with Angle			

	Support. With a 12mm thick machine			
	polished clear glass top fitted to the			
	main structure with 4 nos. 75mm high			
	stainless steel studs.			
17	Suggestion Box & Cheque Drop Box	4	NOS.	
''	FOR BRANCH	7	1403.	
	Providing & fixing Suggestion box of			
	size (450mmm x 150mm x 300mm)			
	made out of 12mm block board			
	finished with 1mm laminate and			
	openable shutter with locking			
	arrangement.			
18	WOODEN LUNCH TABLE IN LAMINATE FINISH	7	RFT	
	Providing and laying Lunch Table 2FT			
	Depth made of approved BWR ply			
	wood 19mm thick supported on			
	wooden legs . The table shall be			
	finished with 1mm laminate and with			
	polished T.W. edge moulding.			
19	WINDOW SCREEN			
	Providing, fitting in position 100mm			
	Vertical blinds made of			
	best quality PVC coated polyester			
	fabric of approved make			
	& shade & to be tailored to the size	150	Sqft	
	of the window.			
20	GYPSUM BOARD FALSE CEILING	450	Sqft.	
	(INCLUDING DROP) in branch		• 4	
	Providing and fixing in position			
	dropped ceiling in two levels			
	including vertical surfaces in			
	between two level of ceiling surface			
	with 12.5mm thick tapered edge			
	gypsum board conforming to			
	IS 2095 including providing and			
	fixing of framework made of			
	special sections power pressed from MS Sheet and galvani-			
	sed in accordance with Zinc coating			
	600 as per IS 277 and			
	costing of angle cleats of size 25mm			
	wide x 16mm thick			
	with flanges of 22mm and 37mm at			
	1200mm center to center			

one flange fixed to the ceiling with	h
dash fastner 12.5mm dia	
with flanges of 22mm and 37mm of	it
1200mm center to center	
one flange fixed to the ceiling with	n
dash fastner 12.5mm dia	
x 40mm long with 6mm dia bolts to	
the angle hangers of	
25x25x5 mm of required length and	d
other end of angle hanger	
being fixed with nut and bolts to G.	
Channels 45mm x 15mm	
x 0.9mm running at the rate of 12mm	n
centre to centre to	
which the ceiling section o.5mn	n
thick botton wedge of 08mm	
with tapered flanges of 26mm each	n l
having clips of 10.5mm at	
450mm center to centre shall be	
fixed in a direction perpen -	
dicular to G.I. Channel with	
connecting clips made out of 2.64	1
mm dia x 230mm long G.I. Wire d	T
every junction including	
fixing the gypsum board with ceiling	
section and perimeter	
channel.	
The perimeter of ceiling fixed to	
wall/partition with the help of rawl	
plugs at 450 mm center to cente	r
with 25mm long drive all screws	
@ 230mm interval including jointing	9
and fixing to a flush	
finish of tapered and square edge	s
of the gypsum board with	
recommended filter, paper tapes	i,
finisher and two coats of	
primer suitable for gypsum board a	s
per manufactures	
specification and also include the	
cost of making openings	
for light fittings grills, diffusers, cutout	,
made with frame of	
perimeter channels of the Engineer	_
in-Charge .	
Rates to include cost of making	<u>, </u>
·	-
openings for ceiling mounted	,
electrical	
fittings/air-conditioning accessorie	5
and also making of openings	

	of size 2'x2' with door for electrical servicing as per instructions.			
20	FALSE CEILING (Armstrong) in Branch		SQFT	
20	& ATM	500	3 Q FI	
	Providing & fixing in position false			
	ceiling in Armstrong Make			
	600 x600 mm x 15/16 mm Dune			
	Microlook file			
	with Regular Black reveal framework			
	as specified by Armstrong Co .			
	with suspenders wherever required. Making cecessary			
	framework for A.C ducting, if any			
	and cecessary cutouts for			
	diffusers and light fittings, taping and			
	finishing to proper line			
	& level, including making grooves			
	and trap doors for A.C			
	unit in 18mm thick M.R. Grade			
	Plywood with Stainless Steel			
	hinges & locks with moulding 1" x 1"			
	for edges including finishing			
	with White Plastic Emulsion Paint etc.			
	complete in all respects.			
	(Note- Only the plan area will be measured for payment.			
	No extra payment will be made for			
	cutouts, grooves mouldings etc.)			
	coroors, grooves modialings ere.j			
21	PLASTIC EMULSION PAINT WORK IN THE AC AREA			
	Providing & applying minimum two			
	coats of acrylic emulsion paint of			
	approved			
	shade & make on a base coat of			
	necessary primer including			
	necessary scrapping			
	of old surface & new surface	1500	SQFT	
	preparation in the walls under false			
	Ceiling.			
	Providing & laying 1mm thk.(avg.) White Cement Putty on the wall area			
	to			
	prepare the surface before Plastice			
	Emulsion paint , as directed by			
	architect.			
22	SYNTHETIC ENAMEL PAINT ON STEEL WINDOWS/WOODWORK/ROLLING	1000	SQFT	

	SHUTTER			
	Providing and painting on wooden,			
	steel or plastered surfaces with two			
	coats of			
	Synthetic Enamel paint of			
	approved shade & brand over a			
	coat of primer of			
	approved quality after sand			
	papering the old/new surface to			
	give an			
	even uniform shade.			
23	DISTEMPER PAINT WORK IN THE NON			
	AC AREA			
	Providing and applying minimum			
	two coats of Distemper paint of			
	approved			
	shade & make on a base coat of			
	necessary primer including			
	necessary scrapping of old surface & new surface	3000	SQFT	
	preparation in the walls under	3000	30(1)	
	ceiling.			
	coming.			
Α	TOTAL EXCLUSIVE OF GST			
		ľ	·	
В	DISCOUNT IF ANY			
C	TOTAL AFTER DISCOUNT (A - B)			
D	GST			
Е	TOTAL INCLUSIVE OF GST (C + D)			

APP	ROVED MAKE OF MATERIALS				
1	False Ceiling / Channels	India Gypsum / Armstrong / Saint Gobain			
2	Wood Frame Work / Wood Section : All Wood, Must be well seasoned, free from knots, other defects decay and defects due to handling and Transportation. Wherever necessary, provide with anti – termite Treatment.	Malaysian Sal / Kapoor			
3	Wood Skirting / Moulding / Lipping / Bidding	White Beach / White Ceader / CP Teak			
4	Wood Preservative	STP Pentaphene Pale / Termiseal by PCI Bison by British Paint			
5	Fire Reterdant Paint	Industrial grads of Noble / Viper			
6	BWP Ply (IS: 710)	Century / Green / Archid / Globe / Sylvan			
7	Flush Door / BWP Block board (IS: 1659)	Century / Green / Archid / Globe / Sylvan			
8	Laminate (1.0 mm thk.) (IS : 2046)	Green lam / Century mica / Sunmica Archidlam			

	-			
9	Door Closure (Heavy Duty)	Godrej / Archi / Sterling (DC 2000)		
10	Floor Spring (Heavy Duty)	Godrej / Archi / Sterling (FS 3000)		
11	Door Lock (Dead)	Godrej / Hafele /Hettich / Kich / Doors Yale		
12	Door Handles	Godrej / Hafele /Hettich / Kich / Doorset		
13	Drawer / Storage Handle	Godrej / Hafele /Hettich / Kich / Doorset		
14	Drawer / Storage Lock (Multipurpose)	Ebco / Hafele /Hettich /Doorset		
15	Night latch	Godrej / 4C Acme		
16	Screws	GKW / Nettle fold		
17	Hinges	CIEF		
18	Sliding Telescopic Drawer Channel	Ebco / Earl Behari / Efficient Gadjets		
19	Cable Organiser	Ebco / Innofitt Systems (CM 63.C)		
20	Adhesive	Fevicol SH / Fevimate TL		
21	Soft Board	Jolly Board		
22	Vertical Blinds	Mac / Annums / Window Fashion		
23	Glass	Modi /AIS / Saint Gobain		
24	Paints (Synthetic Enamel / Acrylic	Asain Paints / Berger / ICI		
	Emulsion)			
25	PVC Flooring	Krishna Vinyl / Armstrong / Birla		
26	Texture Paint	Spectrum		
27	Glass	Modi / AlS / Saint Gobain		
28	European WC / Washbasin	Hindware /Parryware		
29	Sanitary Fittings	Jaquar / Essco Delux		
30	G.I. Pipe	Tata (Medium)		
31	Cement	Ultratech / Laferge / ACC		
32	Footmat	Birla 3M / Approved Equivalent		
33	Vitrified Tiles	Johnson / Naveen / Kajaria		
34	Ceramic Tiles	Johnson / Naveen / Kajaria		
35	Chairs	Godrej/Methodex/Monarch		
36	All other items not covered above	As per sample approved b Employer/Consultant		