

BOQ -INTERIOR WORK - PARDI BRANCH, CANARA BANK, RO-1, NAGPUR.

S.NO.	PARTICULARS	UNIT	QTY.	RATE	AMOUNT
1	Providing & fixing 68mm thick full ht. Full ht. Dead/Partially Glazed partition with 6mm thick MR grade Comm. ply to either side of frame of 50 mm x 50 mm x 1.2mm medium duty hollow Aluminium sections at less than 610 mm c/c in both direction including 6mm thick plain glass with etching film, partially glazed door shutter out of BWR solid core flush door panel, fixing 8 mm thick glass with etching film, 1'0" long S.S. handles, Mortised lock, door closer (OZONE make), door stopper and three coats of French polish of approved shade to TW beading as per drawing. The item also includes grouting frame in wall/ floor & ceiling etc. complete, as per requirement and instructions of bank's engineer. (Al. sections shall carry up to slab soffit. Measurement up to ceiling only will be paid.). Finishing in following ways-				
a	Finished with 1.0 mm thick laminare (in multi colour) of approved shade and make on both side	Sq.m	60		
2	Providing and fixing in position 1.22m to 1.52m high low/medium height partitions including wicker gate, made of 50 x 50 x 1 aluminium square section framed at 0.6m to 0.45mm c/c both ways covered with 6 mm ply and 1.0 mm laminare (in multi colour) of approved shade & make both sides, including all necessary openings/cutting for cheques & other papers & to receive 10mm thick Float glass including all necessary openings for electric / telephonic conduits etc. as per requirement, 10mm thick Float glass with etching as per design, held with SS clits ('D' brackets). All exposed glass with rounded moulding and crystal polish. All exposed woodwork to be finished with 03 coats of french polish.	Sq.m	20		

3	Providing and erecting in position Cash Counter (SWC) as per design & drawings and instructions/directions 900 mm wide, 1200 mm high (Customer side) & 760mm high (Staff side) as per standard design, made out of 19 mm thk. BWR grade ply (confirming to IS 303 of 1989) finished with 1 mm laminate of approved make, shade, colour, texture in directed pattern with free edges covered with TW beading polished of drawers & shelf unit out of 12 mm BWR grade ply for SWC, cable manager, hinges, locks etc. with foot rest and plank for P.C. and readymade metallic keyboard of approved make(EBCO) and all necessary accessories suitably suspended below table top with 0.8 mm thk. Laminate internally etc. complete. The vertical sides finished with approved colour of 1 mm thick decorative mica. The table top to be provided with 20 mm thk. Galaxy black granite on extra raised table top only (ledge of 1'3" width) as per drawing & details etc. complete. Item includes 12 mm thk. Clear Etched glass at Front of banking counters with opening for talking window as per drawing & fixed on side with `D' clips including polishing of all open edges of glass as directed with finishing etc. complete.(Basic Rate of Granite is Rs. 2400/Sq.m.)	Rmt	1.52		
4	Providing and fixing fully glazed door at the Main Entrance pivoted as shown in the drawing, consisting of patch fittings to hold 12mm thk. (Modi guard make) clear toughened etched float glass . All the edges of the glass shall be machine polished. Rate shall include necessary etching to glass, approved locking systems (Ozone/ Godrej make-ultra mortise dead lock), 1 pair of 18" long S. S. Handles, gaskets & miscellaneous hardware items.	sq.m	8		
5	Providing and fixing floor springs Hafelle/ Ozone make BTS 65 V with zero degree open function. The floor spring should be with adjustable closing force and closing speed. Closing action effective form approx 175 degree, with full hydraulic sequential control and back check. Including cement box, replaceable standard spindle and SS cover plate. Non handed; also suitable for double action doors cover plate material and finish: stainless steel of approved make and specification etc. All complete as per detail drawing, as specified and as directed by Architect.(Basic Rate is Rs. 8500)	Nos.	4.00		
6	Providing and fixing Fixed Glazing consisting of patch fittings to hold 12mm thk. (Modi guard make) clear Toughened float glass . All the exposed edges of the glass shall be machine polished. Gap (if any) between two glass panes shall be closed with white silicon sealant. Rate shall include etching flim to glass as per drawing, miscellaneous hardware items. (Heavy Duty Patch fittings – Hafelle/Dorma make).	sq.m	15		
7	Providing and fixing 6mm thk. MR grade Comm. ply with 1 mm thk. Laminate from both sides in multi-colour of existing doors of approved quality and shade with hinges and mortised lock, door closer, door stopper, tower bolt including all necessary fittings & fasteners etc. complete.	Sq.m	12.00		

8	Providing & Fixing in position Ply Boxing cover to Main Electrical Panel with Louvred openable shutter with air vents Grill & T.W. frame & 12 mm th MR grade Comm. ply & 1mm th. Laminate including hinges Locking arrangements complete as per design / direction.	sq.m	4		
9	Providing and fixing suspended False Ceiling (including paint & putty) , as per design and drawing at any height which includes G.I. Perimeter channel (MF6) of size 0.40 mm thick (having one flange of 20 mm and another flange of 30 mm and web of 27 mm) along with perimeter of ceiling, screw fixed to brick wall / partition with the help of nylon sleeves and screws at 610 mm centers. Thereafter suspending G.I. intermediate channel (MF 7) 600 mm. c/c of size 45mm (0.9 mm thick with two flanges of 15 mm each) from the soffit at 450 mm centre with connecting angle (i.e. ceiling angle) of width 25mm x 10mm x 0.40mm thick fixed to soffit with G.I. cleat and teel expansion fasteners. Ceiling sections (MF 5) of 0.55 mm thickness having knurled web of 51.5 mm and two flanges of 26 mm each with lips of 10.5 mm are then fixed to the intermediate channel with the help of connecting clip and in direction perpendicular to the intermediate channel at 450 mm centers. 12.5 mm tapered edge Gyp board (conforming to IS 2095 – 1982) is then screw fixed to ceiling section with dry wallScrews at 230 mm centers. Screw fixing is to be done mechanically with suitable attachment. The boards are to be joined and finished so as to have flush look which includes filling and finishing the tapered & square edges of the boards with jointing compound, joint paper tape and appropriate suitable primer and three coats of plastic acrylic paint. The item includes for light fitting, grill diffusers and cut out etc. have to be made with frame of perimeter channels of size 20mm x 30mm x 0.55mm. thick supported suitable and angle bead is to be used at steps to get straight line finish etc. complete NOTE :- (No extra payment will be done for designs of any width and any length, which are made out of gypsum board). Rate includes making necessary cutouts / opening for light fittings, A. C. diffusers etc. The cutouts to have	sq.m	90.00		
10	Providing & fixing in position Modular false ceiling in (Armstrong or Equivalent make) 600x600 mm x 15/16 mm Dune Supreme Rh 99 Prima tile with Tegular edge framework as specified by Armstrong Co. with suspenders wherever required. Making necessary framework for A.C. ducting, if any, and necessary cutouts for diffusers and light fittings, taping and finishing to proper line & level, including making grooves (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, mouldings etc complete.)	SQ.M	45.00		

11	Providing and fixing as per approved make 100 mm wide vertical fabric blinds (Vista/Hunter Douglas make) complete with handling chain, sliding & tilting system in drawn position, fabric vanes to overlap by minimum 10 mm (every 1 m. length to have at least 12 Nos. 100 mm wide fabric-vanes).Length of blinds bottom end to be at least 12 mm from horizontal surface fabric strip as that of fabric vanes, to be fixed on both sides on Aluminium top channel. Lower end of vanes to be weighed down & tight with each other on both corners with ball chains .Items to be completed in all respects including fixing with brackets on wall or partition with rawl plugs.	sq.m	6.00		
12	Providing & fixing Aluminium Composite panels 4 mm thk. Of exterior grade with 50 x 25 mm size aluminium frame section to External walls/Column surfaces/ cantilever frames at Entrance. Filling joints with silicon sealant, cleaning, scaffolding etc. complete.	Sq.m	40.00		
13	Providing and fixing paneling over Wall/RCC column/ceiling with 12 mm thick commercial ply on aluminium frame work 50 x 25 mm at 300 mm center to center bothways as per design, finished with 1 mm thk. Laminate of approved colour & make. The rate shall include all necessary hardware fittings, etc.	sq.m	100		
14	Tables: Providing & fixing in position tables made of 18/19mm MR grade ply at top, side & front, support along with drawer unit & powder coated metallic keyboard tray, both with telescopic arrangement & CPU base (both Ebco make) footrest of TW member-75X40mm, including 18mm MR grade ply Modesty panel. All external surfaces to be finished with 1mm thk Laminate & internal surfaces finished with 0.80mm laminate of approved shade & make, medium duty hinges for shutter, cable manager, 4" long S.S.Brush finish handles in approved design and locks wherever directed in approved make. All exposed plywood edges to be finished with 10mm thk. TW Beading having 03 coats of French polish in approved shade and necessary locks to shutters etc. complete in all respects.				
a	1820 x 910 x 760 mm (Ch. Manager Table)	Nos.	1		
b	1520 x 750 x 760 mm (Officer Table)	Nos.	4		
c	1350 x 650 x 750 mm (Clerical Table)	Nos.	1		
d	950 x 610 x 760 mm (Store-keeper Table)with 01 drawer & without computer arrangement	Nos.	1		
15	Providing Side/Center Table of size 750x 750x 400 mm in 50x38mm teak wood frame structure as per drawing & design with three coats of Melamine polish of approved shade and 12 mm thick clear etched glass top with beveled edges, fixed with vacuum fixers.	No.	1		

16	Providing & fixing side table of following sizes made of 18 mm thick ply for all top, support and side with 6 mm thick ply at back externally finished with 1.0 mm thick laminate and internal surface shall be finished with 0.8 mm thk. laminate, both of approved make including 4" long brush finish SS handles, shutters hinges with necessary teak wood beading including three coats of French polish to teak wood member and necessary locks to shutters etc. with finishing complete.				
a	1000 x 450 x 760 mm (for Ch. Manager)	No.	1		
b	910 x 400 x 760 mm (For Officers & Clerks)	No.	5		
17	Providing and fixing 425mm deep, 760mm high File Storage Cabinets out of 18 mm thick commercial ply with T.W. beading on edges, 6 mm thick commercial ply on back with one coat of wooden primer, 1 mm thick laminate (multi colour and grooves in laminate as per drawing) on all external surfaces & 0.8 mm thk. laminate on all internal surfaces, 4" long brush finished stainless steel handles, locks, magnets for shutters and three coats of French polish to T.W. beading/ T.W. members as per drawing.	Sqm	7.5		
18	Providing and fixing Writing desk as per bank standardized dwg of size about 910 mm long and 300 to 450 mm width to shape at about 1050 mm from floor level out of 18mm comply boxing on sides of 200 mm height and finished with 1mm thk laminate of approved colour and shade. 12mm clear float glass with edge polished at top and 6 vertical glass dividers to be fixed on ply boxing with with necessary S.S "D" bracket.	Nos.	1		
19	Providing and fixing Cheque drop box & suggestion box as per bank standardized dwg of size about 910mmX400mmX610mm to shape at about 1050 mm from floor level out of 18mm comply boxing on sides of 200 mm height and finished with 1mm thk laminate of approved colour and shade. 12mm clear float glass with edge polished at top and 6 vertical glass dividers to be fixed on ply boxing with with necessary S.S "D" bracket.	Nos.	2		
20	Providing and fixing cushion 2 Seater Sofa with side stool with handles out of 18 mm thick comm. ply structure as per drawing with 100 mm thick high-density foam and upholstery of approved shade and make including three coats of melamine polish to T.W. members (wherever exposed). Basic Rate of Upholstery. Rs. 500. 00/Sq. m.	Nos.	1		
20	Providing & fixing SOFT Boards FABRIC PANELLING 1500 x 910 mm size x 50mm deep, made up of 12 mm soft board fully covered by approved colour upholstery & fixed on 12 mm commercial ply backing & with T.W beading including three coats of French polish of approved shade to T.W. beading and necessary hinges, fixtures & fastenings etc. complete.	Sq. m	15		

21	Providing & fixing Lockable Notice Boards 1500 x 910 mm size x 50mm deep, made up of 12 mm soft board fully covered by approved colour upholstery & fixed on 12 mm commercial ply backing & with sliding shutters out of 5mm thk. Clear glass with locking arrangement and running within required size T.W beading including three coats of French polish of approved shade to T.W. beading and necessary hinges, fixtures & fastenings etc. complete.	No.	1		
22	CABINET FOR ELECTRIC PANEL: Providing, making and placing in position cabinet with openable shutter around the electric panel. Cabinet and shutter made of 18mm thick exterior grade MR commercial plywood All visible surfaces shall be laminated with 1.00 mm thick laminate on external surfaces of approved shades painting the internal surfaces with two or more coats of synthetic enamel paint including providing teakwood lipping of size 20 x 6 mm on edges. Horizontal slots (approx. 10 mm wide) to be cut in the shutter at top & bottom for ventilation. Rate to include for necessary hardware fixture like providing with 3 nos. of 75mm long SS hinges for each shutter, two nos of 75 mm tower bolt (one top and bottom), SS handles to shutters, magnetic catchers for each shutter and multipurpose Godrej or Ebco lock. (Measurement area =	Sq. m	4		
23	Providing & Fixing back-painted (approved colour) Mirror Panelling using 8 mm thick mirror of approved make over BWR IS 303 grade 19 mm Thk Plywood backing, Aluminium framework etc directly to be mounted over the surface or over and including SS studs including making provision for providing LED cove backlit lighting wherever directed, brackets, necessary hardware, fittings, fixtures etc . The mirror to be fixed with T.W beading of size 12.5mm X 19mm, finished with melamine polish complete as per the instructions of EIC. The rate shall be inclusive of providing & fixing S.S studs of appropriate size & diameter as directed including bevelling for the mirror as directed by Architect	Sq. m	10		
SUB TOTAL INTERIOR WORK (without GST)					

GST EXTRA AS APPLICABLE

for S.Nandedkar & Associates
Architect


