	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST I	BULDHANA			
	ALL EDIO CONTRACTOR AND ADMINISTRACTOR AND ADMINISTRACTOR AND ADMINISTRACTOR AND ADMINISTRACTOR AND ADMINISTRACTOR AND ADMINISTRACTOR ADMINISTRACTOR AND ADMINISTRACTOR ADM	1		Г			
	ALL FRLS wires to be used  Type of wiring	Canasal					
	Casing capping (as per approval)	Conceal		ining (ICI are	d a \		
	PVC pipe and accessories			ision (ISI gra	,		
	Wires			ab / Swastik			
	Computer DataCable			/ R R kabel i	nake with		
	cable			Awaya make / R R kabel i	maka (ICI		
	MCB / MCB DB				•		
	ELMCB			Siemens (IS Siemens (IS			
	Ft. tubes & fixtures				avells / Bajaj		
	Ceiling fans / Wall fans / Exhaust Fans				Usha / Bajaj		
	screws	Nettlefol		es / Havelis /	Usna / Bajaj		
		1			-hl		
	Earthing material Switch fuse unit			per and with	спагсоаі		
		L&Tma	, ,	Dame M. I	lastes a		
	Switches/sockets & accessories switchboards			Roma Modu	ııar type		
		Conceal					
	Copper strip type busbar ONLINE UPS	Havells /		a make			
		Fuji / Vei					
	SMF Batteries	Exide / A		-			
	Offline UPS / Inverter	Microtek		S			
	Tubular Batteries	Exide / A	maron	ı			
SR	SUMMARY				AMOUNT		
SK	SUMIMART				AMOUNT		
Α	TOTAL OF MAIN PANEL / DB's / MCCBs :-				_		
В	TOTAL OF CABLES & TERMINATIONS				_		
С	TOTAL OF POINT WIRING						
D	TOTAL OF FIXTURES						
E	TOTAL OF EARTHING SYSTEM						
F	TOTAL OF TELEPHONE SYSTEM						
G	TOTAL OF DATA CABLING SYSTEM						
Н	TOTAL FOR MISCELLANEOUS WORKS						
	TOTAL FOR IMPOLLED AND TOTAL						
	TOTAL FOR ELECTRICAL WORKS						
	TOTAL FOR ELLOTRICAL WORKS	1	1				
J	LESS DISPOSAL & BUYBACK VALUE	<del> </del>	<del>                                     </del>		_		
_			<del>                                     </del>				
	TOTAL FOR ELECTRICAL WORKS	<u> </u>	<u> </u>		_		
		<del> </del>	<del> </del>				
	DISCOUNT OFFERED -	<u> </u>	%		_		
		<u> </u>	1				
	GRAND TOTAL FOR ELECTRICAL WORK				_		
			<u> </u>		GST extra		
	Amount in Rs. : - Rupees	plus (	ST.				
					GST extra		
	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST I	BULDHANA			
NO.	ITEM	UNIT	QTY	RATE	AMOUNT		
140.		31411	<u> </u>	IVAIL	AMOUNT		

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST E	BULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
	MAIN PANEL / DISTRIBUTION BOARDS /				
Α	MCCBs:-				
1	Meter room Mains MCCB's				
	Supplying & Installing 80A / 100A, FP MCCB in				
	Sheet Steel Enclosure, complete with Gland				
	Box etc				
	a. 80A / 100 A FP MCCB 16kA	Nos.	1.00		_
	Make: Legrand, Type: DPX3 160 with Thermal &	1403.	1.00		
	Magnetic protection Unit				
	b. Sheet steel Enclosure Box for FP MCCB	Nos.	1.00		_
2	MCB DISTRIBUTION BOARDS				
	SITC sheet metal fabricated & powder coated				
	Double Door Type MCB Distribution Boards				
	(surface/flush mounted). DB's shall have				
	MCB/MCCB as incomer, RCCB as sub-incomer &				
	SP/DP/TP MCB as outgoing, complete with Per Phase Isolation. All MCBs of C characteristics and				
	10 KA breaking capacity & ELCB's, RCCB's,				
	RCBO's should be of 100mA sensitivity. The DB				
	shall have appropriate no. of top & bottom knock				
	outs for outgoing circuits & shall be complete with				
	necessary bus bars, interconnecting terminals &				
	earth studs. All terminations in DB shall be				
	complete with feruling, dressing with lugs & all				
	circuits shall be properly labeled with PVC strip				
	(sticker type) having identification as per the final				
	approval of the Consultant.				
	SITC Mains DB,				
	6 way VTPN - MCCB DB,	Nos.	1.00		-
	80/100 A - TP MCCB, 16kA	Nos.	1.00		1
	25 A - TP MCB outgoing (LDB)	Nos.	2.00		-
iv)	63 A - TP MCB outgoing (AC DB & Spare)	Nos.	2.00		-
,	25/32 A - SP MCB outgoing (UPS Input / Inverter	Nice	0.00		
,	DB, Signage / ATM DB)	Nos.	6.00		-
VI)	Blanking plates	Nos.	0.00		-
2.2	SITC LIGHTING DB		†		
	6 way TPN - MCB DB,	Nos.	1.00		-
,	25 A - FP MCB, as incomer	Nos.	1.00		-
	25 A - DP 30mA RCCB / ELCB, as sub-incomer	Nos.	3.00		-
iv)	6/10 A - SP MCB outgoing	Nos.	12.00		-
0.0	CITC DAW DOWED & AC DD				
	SITC RAW POWER & AC DB	NI	4.00		
	6 way TPN - MCB DB,	Nos.	1.00		-
II)	63 A - TPN MCB	Nos.	1.00		-
:::\	40 A - DP 100mA RCCB / ELCB, as sub-	Nes	2.00		
III)	incomer	Nos.	3.00		-

	SOQ FOR ELECTRICAL WORKS AT MALKAPUI	RBRANC	H DIST B	ULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
iv)	16/20/25/32 A - SP MCB outgoing	Nos.	12.00		-
-					
2.4	SITC UPS Output DB				
	6 way SPN - MCB DB,	Nos.	1.00		-
	32 A - DP MCB as incomer	Nos.	1.00		-
iii)	32A - SP MCB outgoing, for Branch UPS DB	Nos.	2.00		-
	16A - SP MCB outgoing, for CCTV, Network				
iv)	rack, Security alarm system etc	Nos.	2.00		-
2.5	SITC BRANCH UPS DB				
i)	16 way SPN - MCB DB,	Nos.	1.00		-
	32 A - DP MCB as incomer	Nos.	2.00		-
iii)	16/20A - SP MCB outgoing	Nos.	10.00		-
,		1			
2.6	SITC INVERTER Lighting DB	<u> </u>			
	16 way SPN - MCB DB,	Nos.	1.00		-
	25 A - DP MCB as incomer	Nos.	1.00		-
	6/10A - SP MCB outgoing	Nos.	12.00		-
2.7	SITC ATM LDB / AC DB				
	6 way SPN - MCB DB,	Nos	1.00		-
	32 A - DP MCB as incomer	Nos	1.00		-
,	10/16/20A - SP MCB outgoing	Nos	3.00		-
2.8	SITC ATM UPS Output DB				
	6 way SPN - MCB DB,	Nos.	1.00		_
	16/20 A - DP MCB as incomer	Nos.	1.00		_
	10/16A - SP MCB outgoing	Nos.	1.00		-
2.9	MCB BOX				
	SITC 4 way - MCB with Box, for switching off				
	the lighitng DB near main gate to switch OFF all				
a.	the light points after office hours				
i)	Sheet steel Enclosure Box for FP MCB	Nos.	0.00		-
ii)	32/25 A - FP MCB	Nos.	0.00		-
	SITC 4 way - MCB with Box, for switching off				
	the AC DB near main gate to switch OFF all the				1
b.	AC's after office hours				<u>                                      </u>
i)	Sheet steel Enclosure Box for FP MCB	Nos.	0.00		-
ii)	63 A - TPN MCB	Nos.	0.00		-
С	SITC 2 way - MCB with Box, for Cassette AC,				
	at Out Door Unit	<u> </u>			
	Sheet steel Enclosure Box for DP MCB	Nos.	4.00		-
ii)	32 A - DP MCB	Nos.	4.00		-

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST B	ULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
d	SITC 2 way - MCB with Box, for UPS Input /				
	Output and for switching OFF UPS outputs to				
	branch				
i)	Sheet steel Enclosure Box for DP MCB	Nos.	3.00		-
ii)	<b>32/25 A -</b> DP MCB	Nos.	3.00		-
е					
	SITC 2 way - MCB with Box, for Signage and for				
	switching OFF Inverter outputs to branch				
i)	Sheet steel Enclosure Box for DP MCB	Nos.	2.00		-
ii)	<b>20/25 A -</b> DP MCB	Nos.	2.00		-
3	Signage Timer				
	Supplying and Installing programmable <b>Digital</b>	No.	0.00		-
	<b>Timer</b> microcontroller based with real time clock to				
	operate on derived switching "ON" and switching				
	"OFF" glow sign board light as per daily sunset and				
	sunrise respectively automatically having 4 digit				
	LED continuous time display erected in M.S.				
	box.				
4.0 a)	Supplying & Installing 10/20 A Modular Power	Nos.	4.00		-
-	Socket points complete with MS concealed box,				
	Modular Switch plate, <b>20A Modular Socket</b> ,				
	controlled by a Modular 20 / 25A SP MCB with				
	necessary screws, nylon plug, Saddles, hardware				
	etc. including cost of 3 x 4.0 sqmm PVC				
	insulated FRLS copper Wires and 25mm/20 mm				
	PVC conduit, For ATM UPS & Inverter Input &				
	Output connections				
	Rate in words : -				
-	Supplying & Installing 20 A Power Socket	Nos.	3.00		-
	points complete with MS concealed box, 20A				1
	Modular Socket, without local switch (directly				
	controlled by a 20 / 25A SP MCB in AC DB) with				
	necessary screws, nylon plug, Saddles, hardware				1
	etc. For High Wall Split AC Units				
	including cost of 2x4.0 sqmm + 1x2.5 sqmm PVC				
					Ī
	insulated FRLS copper Wires and 25mm/20 mm				
	insulated FRLS copper Wires and 25mm/20 mm PVC conduit, For High Wall Split AC Units				
	PVC conduit, For High Wall Split AC Units				
	• •				

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST B	<u>ULDHANA</u>	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
d)	Supplying & laying circuit wiring for 20 A Power Socket points (without any socket / switch (directly controlled by a 20 / 25A SP MCB in AC DB) with necessary screws, nylon plug, saddles, hardware etc. by laying 2x4.0 sqmm + 1x2.5 sqmm PVC insulated FRLS copper Wires	Nos.	4.00		-
	through 25mm/20 mm PVC conduits, <i>For Cassette AC Units</i> including cost of 2x4.0 sqmm + 1x2.5 sqmm PVC				
	insulated FRLS copper Wires and 25mm/20 mm PVC conduit, For Cassette AC Units				
	Rate in words : -				
	STRONG ROOM SUPPLY				
e)	Supplying & Installing 20 A Power Socket points complete MS concealed box, Modular Switch plate, 20A Modular Socket, controlled by a Modular 20A SP MCB with necessary screws, nylon plug, Saddles, hardware etc. including cost of 2x2.5.0 sqmm + 1x1.5 sqmm PVC insulated FRLS copper Wires and 25mm/20 mm PVC conduit, For Strong Room / Cash room Entrance as It's Lighting circuit control from outside. Lighting switch board inside the Strong room / Cash room to be connected using, 2 mets of 3 core 1.5 sq mm flexible copper cable with 15 A plug top from this power socket installed outside the room ( rate should be given inclusive of flexible cable, plug top and circuit )	Nos.	1.00		
	Rate in words : -				
	A. TOTAL OF MAIN PANEL / DB's / MCCBs :-				0.00
	OADLEG & TERMINATIONS				
В	CABLES & TERMINATIONS  Supply and Laying of following LT cables confirming to IS 1554 (part 1) with necessary M.S. clamps. All such cables shall be provided with temporary labeling at every 20 mtr. & then finally with metal identification tags showing the size & the location from/to the specific panel/DB; at both the ends. The rate is inclussive of termination charges				
	Aluminium Armoured Cables		400.00		
a.	4 C x 50 Sq.mm Aluminium AYFY Armoured Cables, from MSEB Meter to Main Power DB	Rmt	100.00		
	Rate in words : -				

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST B	ULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
2	Copper Flexible Cables				
a.	3C x 4 Sq.mm Copper Flexible Cables, from UPS Output to UPS DB Input MCB	Rmt	60.00		-
	Rate in words : -				
b.	3C x 6 Sq.mm Copper Flexible Cables, for UPS Input	Rmt	40.00		-
	Rate in words : -				
	1C v 1 Ca mm Conner Flovible Cobles from Main	Dmt	FO 00		
C.	4C x 4 Sq.mm Copper Flexible Cables, from Main  DB to Lighting DB	Rmt	50.00		
	Rate in words : -				
٦	4C v 6 Sq mm Copper Florible Cobles from Maine	Dmt	90.00		
a.	4C x 6 Sq.mm Copper Flexible Cables, from Mains DB to AC Power DB and Main DB to UPS Input MCB	Rmt	80.00		-
	Rate in words : -				
e.	3 C x 2.5 sq.mm. Cu flexible cables, for Signage	Rmt	160.00		-
	and Inverter Input / outputs Rate in words : -				
	B. TOTAL OF CABLES & TERMINATIONS				-
С	POINT WIRING				
1	POWER POINTS				
	SITC of following concealed Power Point Wiring using 1100V grade 3C x 2.5 sq.mm. PVC				
	insulated, PVC Sheathed White Colored flexible				
	copper FRLS cable, laid through 20mm / 25mm				
	size MMS Grade, PVC conduits. All cabling /				
	conduiting below false ceiling shall be concealed.				
	Each circuit feeding not more than 3 Tables / Work				
	Stations). The rate shall include cabling including				
	conduit cost from DB to mentioned Power Points.				
	(No seperate measurements for circuit wiring & PVC Conduits)				
	ar vo conduns)				
			40.00		
a.	Primary UPS points Rate in words : -	No	10.00		-
	Supplying & Installing Primary UPS or Stabilized		<u> </u>		
	Power points on workstations / tables for				
	computers using 3C x 2.5 Sq.mm PVC sheathed				
	white color flexible copper FRLS cable pulled				
	through 25mm size MMS Grade PVC conduites,				
	laid on surface above false ceiling and taken upto				
	table top using 25/20 mm size MMS Grade PVC				
	rigid or flexible conduits run within wooden or metal				
	partitions.				

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANCI	I DIST E	BULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
	Each point consisting of 2 Nos of 6A, 5 Pin Modular sockets and 1 No. of 6/16A, 6 pin socket controlled by 1 No 20A Modular switch, wired together forming one point. Earth wire to be of Green colour only. Switch should be above table top & sockets should be below table top				
	Only 3 tables served by one circuit from UPS DB. The Rate should be including the cost of Conduits, Cables, Switch boards, internal looping wires, necessary Gang Box, PVC box, Modular Plates of other color, Modular Switches, Sockets, Compete Job with necessary screws, nylon plug, Saddles, hardware. Etc. All Switch Boards should be Properly numbered for identifications.				
	Consider UDC nainte	No	F 00		
D.	Secondary UPS points Rate in words : -	No	5.00		-
	Stabilized Power points on workstations / table for computers using 3C x 2.5 Sq.mm PVC sheathed white color flexible FRLS copper cable pulled through 25mm size MMS Grade PVC conduites, laid on surface above false ceiling and taken upto table top using 25/20 mm size MMS Grade PVC rigid or flexible conduits run within wooden or metal partitions.				
	Each point consisting of 2 Nos of 10A, 5 Pin Modular sockets and 1 No. of 6/16A, 6 pin socket controlled by 1 No 20A Modular switch, wired together forming one point. Earth wire to be of Green colour only. Switch should be above table top & sockets should be below table top				
	for 2 table served by the same circuit from adjascent Primary point. The Rate should be including cost of Cable, Switch board internal looping wires, necessary Gang Box, PVC box, Modular Plate of other color, Modular Switches, Sockets, Compete Job with necessary screws, nylon plug, Saddles, hardware. Etc. All Switch Boards should be Properly numbered for identifications.				
c.	Primary 10/20 A power points, for Printers / Cash counting machine / Water cooler / etc Rate in words:	No	3.00		-
	Thate in Words .				

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANCI	H DIST E	BULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
	Supplying & Installing Primary 10/20 A Power				
	Socket points using 2 X 4.0 Sq.mm. + 1 X 1.0				
	Sq.mm. PVC insulated multistanded FRLS Grade				
	flexible copper wires				
	(with proper color code) pulled through haevy				
	gauge PVC conduits.				
	Each point consisting of 1 Nos of 10/20 A				
	Modular sockets controlled by 1 Nos of 20A				
	Modular switch, wired together forming a point.				
	Earth wire to be of Green colour only.				
	Only 2 Sockets served by one circuit taken from				
	Raw Power & AC DB				
2	LIGHT POINT WIRING				
	SITC of following concealed point wiring using				
	1100V grade 3C x 1.5 sq.mm. copper conductor				
	PVC insulated <b>FRLS wires</b> (with proper R,Y,B				
	colour code) pulled through 25mm / 20mm Size,				
	MMS Grade PVC conduits. All wiring below false				
	ceiling shall be concealed. The wires from ceiling				
	junction to light points shall be drawn in flexible				
	PVC conduit with adaptor & cover for junction box				
	& crimp type lugs at both ends. Each circuit				
	feeding not more than average 12 points (800				
	watts). The rate shall include circuit wiring (2C x				
	2.5 sq.mm. + 1C x 1.0 sq.mm.) from Lighting DB to				
	switchboard and to the fixtures. (No seperate				
	measurements for circuit wiring & PVC				
	Conduits)The First Point will be considered as				
	Primary Point and balance points as Secondary Points.				
	Secondary Forms.				
		M-	00.00		
а.	Primary Light points, on LDB  Rate in words:-	No	22.00		-
	SITC 5A Primary light points including MS				
	concealed box, grid plate, 6A switch & circuit wiring				
	through LDB				
	oag.: 255				
b.	Primary Light points, on Inverter	No	15.00		-
	Rate in words : -				
	SITC 5A Primary light points including MS				
	concealed box, grid plate, 6A switch & circuit wiring				
	through Inverter DB				
	On any law 12 of 4 or 2 of 5	NI.	5.00		
C.	Secondary Light points	No	5.00		-
	Rate in words : -		1		
	SITC 5A Secondary light points looped from				
	primary light point. All MCB controlled light points				
	will be considered as secondary light points.				

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST B	ULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
d.	Primary 5 A socket points	No	2.00		
	Rate in words : -				
	SITC Primary 5 A Socket points using circuit				
	wiring (with proper color code) pulled through				
	medium gauge PVC conduits.				
	Each point consisting of 1 Nos of 5 A sockets				
	controlled by 1 Nos of 6A switch, wired together				
	forming a point with Green colour Earth wire.				
e.	Secondary 5 A socket points (on Board plug	No	13.00		
	points)				
	Rate in words : -	ı			
	SITC <b>Secondary 5 A Socket points</b> using circuit				
	wiring (with proper color code) pulled through				
	haevy gauge PVC conduits. These points are				
	installed on the Lighting Switch Board.				
	Each point consisting of 1 Nos of 5 A sockets				
	controlled by 1 Nos of 6A switch, wired together				
	forming a point. Earth wire to be of Green colour				
	only.				
f.	Exhaust fan points Rate in words : -	No	4.00		
			Т		
	SITC of concealed point wiring for Exhaust fan				
	using 1100V grade 3C x 1.5 sq.mm. copper				
	conductor PVC insulated FRLS wires				
	(with proper R,Y,B colour code) pulled through				
	25mm / 20mm Size, MMS Grade PVC conduits.				
	All wiring below false ceiling shall be concealed.				
	The wires from ceiling junction to fan points shall be drawn in flexible PVC conduit with adaptor &				
	cover for junction box & crimp type lugs at both				
	ends. The rate shall include circuit wiring (2C x 2.5				
	sq.mm. + 1C x 1.0 sq.mm.) from Lighting DB to				
	switchboard and to the Exhaust fan and Wall fan.				
	(No seperate measurements for circuit wiring &				
	PVC Conduits)				
	1 vo conduits)				
	Each Exhaust Fan will be operated on seperate				
	switch, Rate should be including the cost of 5 A				
	switch, 4 way closed 5A connector & Mounting				
	Plates(Rates includes Primery light point or				
	Invertor point are same)				
-	Wall Fan points on Inverter	No	5.00		
9.	Rate in words : -	140	0.00		
	SITC of concealed point wiring for Wall fan using				
	1100V grade 3C x 1.5 sq.mm. copper conductor				
	PVC insulated FRLS wires				

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	RANCH DIST BULDHANA				
NO.	ITEM	UNIT	QTY	RATE	AMOUNT	
	(with proper R,Y,B colour code) pulled through					
	25mm / 20mm Size, MMS Grade PVC conduits.					
	All wiring below false ceiling shall be concealed.					
	The wires from ceiling junction to fan points shall					
	be drawn in flexible PVC conduit with adaptor &					
	cover for junction box & crimp type lugs at both					
	ends.					
	The rate shall include circuit wiring (2C x 2.5					
	sq.mm. + 1C x 1.0 sq.mm.) from Lighting DB to					
	switchboard and to the Exhaust fan and Wall fan.					
	(No seperate measurements for circuit wiring & PVC Conduits)					
	Each wall fan will be operated on seperate switch,					
	Rate should be including the cost of 5 A switch, 5					
	A socket, gang box & Mounting Plates(Rates					
	includes Primery light point or Invertor point are					
	same)					
h	Wall Fan points without Inverter	No	4.00		_	
	Specifications similar to above	INO	4.00		_	
	Opecinications similar to above					
i.	Ceiling fan points	No	4.00		-	
	Rate in words : -					
	SITC Ceiling Fan point operated on seperate					
	switch shall be Controlled by 2 Module, Step type					
	Fan regulator, Rate should be including the cost of					
	Fan hook, Suspending suitable fan rod,					
	Connecting cord and Step type Fan Regulator					
j.	Bell points	No	2.00		-	
	Rate in words : -					
	SITC Bell point consisting of 5A Modular Bell					
	switch & Suitable Bell, (Bell switch to be installed					
	in Manager Cabin and in Strong room. The Sound					
	of both the bells should be different )					
			4.00			
K.	Indicator Light points	No	4.00		-	
	R-Y-B Indicator Light point from Main Power DB to					
	Banking area, for indication of Mains power supply					
	with wiring, indicator lamps etc., easily visible from					
	the Exit / Entrance Door, so that the Last Person to					
	leave the Branch / office should Turn OFF the					
	Power Supply (MCB) Located in Power DB's to					
	switch Off the Lighting, fans, AC's etc.					

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANCI	1 DIST E	BULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
	Each Indicator Light Point Wiring to be done with 3				
	X 1.5 Sq.mm. PVC insulated multistanded FRLS				
	Grade flexible copper wires / 3 core 1.5 sq.mm				
	flexible cable drawn through Heavy gauge PVC				
	conduit from Respective DB Power to the				
	Respective Colored Indicator Lamp.				
	Raw Power to be written / Identified on the				
	respective DB with Red Colour				
	UPS Power to be written / Identified on the				
	respective DB with Yellow Colour				
	Lighting Power to be written / Identified on the				
	respective DB with Blue Colour Inverter Power to be written / Identified on the				
	respective DB with Green Colour				
	Rate in words : -	I			
		1			
	C. TOTAL OF POINT WIRING				
	O. TOTAL OF FORME WINING				-
<u>r</u>	EIVTUDES				
D	FIXTURES				
	SITC of following concealed / surface mounted				
	fixtures of makes as specified with all fixture				
	accessories like suitable tubes/ bulbs/ ballast &				
	internal wiring etc. The contractor has to assemble				
	& install the said fixtures at position with necessary				
	hardware required for installation like S-hook,				
	chain link etc. as per requirement.				
4	LED tube lights Al	No	0.00		
1	LED tube lights 4' Rate in words : -	INO	8.00		-
	2.12				
	SITC 1200 mm Long Surface/Wall Mounted				
	extruded Aluminium channels, with 20 w LED				
	Tube light fixtures complete. Rate should be				
	including the cost of Fixture, Suspending suitable				
	rods, other accessories & hardware etc.				
	Make - Dhilips Madel - DN024   FD250 6500 DCI   CD				
	Make: Philips, Model: BN021 LED25S 6500 PSU GR S1,				
	Make: Crompton Model: Linea LDLL20-CDL, LDLL20-				
	WW   Make: Wipro, Model : Garnet D532065, D552065				
	·				
	Make: Havells Model: E-Lite LED Pride Pus				
	LHEXBLP7PN1W020				
2	LED tube lights 2'	No	3.00		-
	Rate in words : -		2.00		
	SITC 600 mm Long Surface/Wall Mounted				
	extruded Aluminium channels, with 10 w LED				
	Tube light fixtures complete. Rate should be				
	· · ·				
	including the cost of Fixture, Suspending suitable				
	rods, other accessories & hardware etc.				
			1		

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST B	ULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
4	18 w Down lighter with LED	No	17.00		-
	Rate in words : -		•		
	SITC 18 w White Powder Coated Housing LED				
	Round / Square Down Lighter with High Efficiency				
	LEDs & Ballasts				
	Make: Philips, Model: DN193B LED12S-6500 PSU WH S1				
	Make : Crompton, Model : PEARL LSCRM-18W-CDL, LSCSM-18W-CDL/NW/WW, LSDRM -18W-CDL,				
	Make: Wipro, Model: CRDL10R015HP40 17W				
	Make: Havells, Model: LHEBJNP7PZ1W018				
5	600 x 600 mm square LED panel fittings	No	14.00		-
	Rate in words : -				
	SITC 36 / 40 w LED Panel of 600mm X 600mm				
	size, Square, Powder coated Recess mounting				
	LED Light Fitting				
	Make: Philips, Model: RC380B G2 LED28S / RC140B				
	G2 LED31S-6500 PSE OD WH  Make: Crompton, Model: LCTLR-36-CDL 36 w, LCPL-				
	36-TL(2X2)				
	Make: Wipro, Model: Gartnet D424065, D414065				
	CRCO10R038HP57				
	Make: Havells, Model: Venus Neo				
	PLR36WLED865PO, Plano PLR42WLED865S				
6	Fono				
6	Fans				
	Supplying & Installing following mentioned Aluminum, medium duty, powder coated with				
	glossy color Ceiling Fans / Wall Fans / Exhaust				
	Fans with necessary clamps hook, bracket,				
	hardware etc				
a.	SITC 1200 mm sweep Ceiling fans Complete with	No	4.00		-
	Mounting rod, Clamps, Locking pin etc. (Color -				
	White / Ivory / Brown)				
	Rate in words : -				
b.	SITC 900 mm sweep Ceiling fans Complete with	No	0.00		-
	Mounting rod, Clamps, Locking pin etc. (Color -				
	White / Ivory / Brown)				
	Rate in words : -				
C.	SITC 250mm sweep Exhaust fan of metal body &	No	3.00		-
	blade with louvers on the outside				
	Rate in words : -		1		
,	0170 400 14 11 ( ( 250 551 1	N 1	0.00		
d.	SITC 400mm sweep Wall fan of 1350 RPM.	No	9.00		-
	Oscillating type, Metal Body & blades chrome				
	plated guard with speed regulator and moisture				
	proof treatment to winding and with 'E' class insulation.				
	JirioulatiOH.				<u> </u>

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANCI	I DIST E	BULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
	Rate in words : -				
	D. TOTAL OF FIXTURES				-
Е	EARTHING SYSTEM				
1	Plate Earthing				
	S & I of Earthing Pit / Earth Electrode Station into the true ground level by using GI / Copper Plate type earthing with necessary excavation in soft soil, including Pouring Charcoal & Salt (Approximately) 50kg each per Pit with Predrilled 50mm dia B class GI Pipe-2.5 Mtr In length, GI Funnel with wiremesh, 35 x 5mm GI/Cu Earthing Strip, Complete job with necessary construction of appropriate sized Earthing PIT masonary Chamber with providing CI hinged chamber cover, Nutbolts, Earthing Testing Link, Hardware, Numbering of Chamber by using water proof paint. For more details refer IS 3043-1987 Brazing for Cu & Welding for GI Plate to pipe & Strip shall be done with coating by anti-corrosive paint				
a.	GI Plate earthing. Rate in words:	No	0.00		-
	GI earthing pit made up of 600 x 600 x 6 mm thick, Hot dipped galvanized electrode including 25 x 5 mm the. GI strip.				
b.	CU Plate earthing or bore earthing	No	4.00		_
	Rate in words : -				
	Copper earthing pit made up of 600 x 600 x 3 mm thick, copper electrode including 25 x 5 mm Copper strip.				
2	Earthing Wires				
_	SITC of insulated copper earthing wire laid through 20 mm PVC conduits from separately made earth pit to the equipment in following sizes				
a.	Single core, 4 sqmm FRLS PVC insulated multi threaded, flexible copper wire laid through 20 mm size, MMS Grade PVC Conduites for Raw Power Earthing.	Rmt	90.00		-
	Rate in words : -		,	ļ	
b.	Single core, 6 sqmm FRLS PVC insulated multi threaded, flexible copper wire laid through 20 mm size, MMS Grade PVC Conduites for UPS power Earthing.  Rate in words:	Rmt	60.00		-
	INAIC III WOIGS				

	Q FOR ELECTRICAL WORKS AT MALKAPUR BRANCH DIST BULDHANA				
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
3	Main Earth Bus	No	2.00		-
	Supplying & Installing of Main bus for isolated earth				
	comprising of 200mm x 40mm x 6mm thick copper				
	bar fixed on insulated support and having 20 nos of				
	holes and				
	nut bolts studs for clamping the earth leads,all contained in MS/PVCbox of size 300mm x 200mm				
	x 50mm deep and having transparent acrilic				
	inspection cover as approved by Bank / Architect.				
	and position devel de approved by Bank, 7 homest.				
	Rate in words : -		1		
	E. TOTAL OF EARTHING SYSTEM				-
	TELEPHONE (VOICE CARLING AND OUTLETS				
F.	TELEPHONE / VOICE CABLING AND OUTLETS				
1	Telephone points	No	1.00		_
	Rate in words : -				
	Providing and laying 2 Pair Grey Color 0.5mm				
	Tinned Cu, PVC insulated cable for Telephone /				
	Voice, laid through 20 / 25 mm size, MMS Grade				
	PVC Conduites and Supplying & terminating with				
	RJ-11 Telephone Jack / Outlet with face plates in				
	suitable modular PVC / MS box from EPABX /				
	Krone Tag Box to the work stations and terminate				
	the other on a 10 pair Krone module installed in a				
	Krone Tag box, complete with numbering of each				
	cable with Ferule and Telephone Connection Chart				
	(No seperate measurements for PVC Conduits)				
	Conduits)				
2	Telephone cables				
	Providing, laying and connecting PVC insulated				
	copper telephone cable, laid through laid through				
	20 / 25 mm size, MMS Grade PVC conduites of				
	following sizes including termination. (No seperate				
	measurements for PVC Conduits)				
a.	10-pair x 0.5 mm size Telephone cable, for	Rmt	0.00		
	MTNL / BSNL mains				
	Rate in words : -				
b.	20-pair x 0.5 mm size Telephone cable, for Floor	Rmt	0.00		
	EPABX lines interconnections				
	Rate in words : -				
3	Telephone krone tag box				

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR	BRANC	H DIST B	ULDHANA	
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
	Providing and fixing of <b>20 pair Krone Tag box</b> / 10	No	0.00		7
	pair Krone type connector module housed in a		0.00		
	Powder coated GI box with lockable cover of				
	suitable size including termination complete with				
	numbering of each cable with Ferule and a				
	Telephone Connection chart.				
	Rate in words : -		•		
	F. TOTAL OF TELEPHONE SYSTEM				-
G	DATA CABLING SYSTEM				
1	Data points	No	9.00		-
	Rate in words : -				
	Supplying and laying D-Link / Molex / Awaya /				
	Amps make, Cat 6 cable for Data, laid through				
	20/25 mm size, MMS Grade PVC conduites and				
	providing & terminating with RJ-45 Information				
	Outlet Ports with face plates in suitable modular				
	PVC / MS box from Server Rack/ Patch Panel/				
	Data Switch to individual work stations &				
	terminating other end with RJ-45 connector				
	including numbering with ferule (No seperate				
	measurements for PVC Conduits)				
	Own Live O Levine Oct O D L 45 Ave Level	NI.	40.00		
2	Supplying & laying Cat-6, RJ-45, 1 m. length	No	10.00		-
	Data Patch Cords,  Make: D-Link / Molex / Awaya				
	Rate in words : -				
3	Supplying & laying Cat-6, RJ-45, 2 met length	No	9.00		_
	Data Patch Cords.	110	0.00		
	Make: D-Link / Molex / Awaya				
	Rate in words : -		1 1		
4	Patch panel				
а	Supplying and Installing D-Link make, preloaded,	No	1.00		-
	Cat-6, RJ-45, 24 Port Patch Panel, complete with				
	terminations & numbering with ferule				
	Rate in words : -				
5	Supplying & Installing D-Link / HCL / iBall make 12-	No	1.00		-
	U Networking Wall mounting rack, complete with				
	following mentioned accessories				
	* 2U Horizontal Cable Manager				
	* Power Distribution Unit / Power Strip of 6 Sockets				
	* Cooling Fans				
	* Cantilever Trays / Shelves				
	* Hardware Packet				
	1				1

	SOQ FOR ELECTRICAL WORKS AT MALKAPUR BRANCH DIST BULDHANA				
NO.	ITEM	UNIT	QTY	RATE	AMOUNT
	Rate in words : -				
	G. TOTAL OF DATA CABLING SYSTEM				-
Н	MISCELLANEOUS WORKS				
	_				
	Arranging temporary Power, data supply & Lighting for all agencies and for staff PCs at work place. The rate shall include statutary aproval from Local MSEDCL / Electrical Inspectorate & other required satatutary bodies, preparation of AS-BUILT drawings, Testing of the installation & preparaition of test report as required by statutary bodies. Note: The rate to include cost of suitable temporary Lighting for all areas as per requirement during work.		1		0
					-
	II TOTAL FOR MISSELLANGOUS WORKS				
	H. TOTAL FOR MISCELLANEOUS WORKS				-
	TOTAL FOR ELECTRICAL WORKS				_
	GST CGST 9%			-	
		SGST 9%			-
	GRAND TOTAL				-