

| Detailed Interior Works BOQ of Proposed Renovation of Canara Institute of Bank Management (CIBM), Ananthnagar Stage 2 Manipal, Udipi District | | | | | |
|--|---|-------|--------|------|--------|
| Sl. No. | Description | Qty. | Unit | Rate | Amount |
| 1 | COMPUTER TABLE FOR LAB : 2 (FOR UPPER GROUND FLOOR) (2 SEAT) | | | | |
| | SIZE : | | | | |
| | 2.40MTS. X 0.76MTS. X 0.60MTS. - 17NOS. | 31.01 | SQ.MT. | | |
| | Providing & Supplying of Computer Table for Lab. Made out of 25mm x 25mm MS Square Tube (Medium Guage) for the Legs, 20mm x 20mm MS Square Tube for top frame, sides, foot rest supports. The Table shall be 18mm thick BWP Grade Plywood for the top, modesty frame, (front & side modesty shall be 3.00 mmm thick (5mm dia. holes) MS Perfo Sheet with SS Studs) Keyboard tray, side supports. All the visible surface shall be 1.00mm thick Laminate of Approved color & shade (Premium Grade) and other surafe shall be 0.80mm thick Laminate of approved colour & shade. The MS Leg shall be with leveller bush , Keyboard on easy sliding Telescopic slider with WireManager. All the Metal surface shall be Powder Coated as per approved colour & Shade . (The Rate shall be required with all materials, labour, transport etc.) | | | | |
| 2 | COMPUTER TABLE FOR LAB : 3 (FOR UPPER GROUND FLOOR) | 19.69 | SQ.MT. | | |
| | SIZE : | | | | |
| | " L " SHAPE | | | | |
| | 4.66MTS + 1.66MTS. X 0.76MTS. X 0.60MTS. - 1NO | | | | |
| | 5.14MTS. + 2.24MTS. X 0.76MTS. X 0.60MTS. - 1NO. | | | | |
| | " STRIGHT " | | | | |
| | 4.73MTS. X 0.76MTS. X 0.60MTS - 1NO. | | | | |
| | 7.48MTS. X 0.76MTS. X 0.60MTS. - 1NO. | | | | |
| | Specification as per Sl. No : 1 | | | | |
| 3 | 4 SEAT READING TABLE : (FOR UPPER GROUND FLOOR) | 95.26 | SQ.MT. | | |
| | SIZE : | | | | |
| | 1.22MTS. X 1.22MTS. X 0.60MTS. -4NOS (1 SET) - 16NOS. | | | | |
| | Providing & Supplying of 4 Seat Reading Table Made out of 25mm x 25mm MS Square Tube (Medium Guage) for the Legs, 20mm x 20mm MS Square Tube for top frame, sides, foot rest supports. The Table shall be 18mm thick BWP Grade Plywood for the top, top dividers . All the visible surface shall be 1.00mm thick Laminate of Approved color & shade (Premium Grade) and other surafe shall be 0.80mm thick Laminate of approved colour & shade. The MS Leg shall be with leveller bush , All the Metal surface shall be Powder Coated as per approved colour & Shade . (The Rate shall be required with all materials, labour, transport etc.) | | | | |
| 4 | 2 SEAT READING TABLE : (FOR UPPER GROUND FLOOR) | 8.93 | SQ.MT. | | |
| | SIZE : | | | | |
| | 1.22MTS. X 1.22MTS. X 0.91MTS. - 6NOS. | | | | |
| | Specification as per Sl. No : 3 | | | | |
| 5 | COMPUTER TABLE FOR LIBRARY : (FOR UPPER GROUND FLOOR) | 12.77 | SQ.MT. | | |
| | SIZE : | | | | |
| | 2.40MTS. X 0.76MTS. X 0.60MTS. - 7NOS. | | | | |
| | Providing & Supplying of Computer Table for Lab. Made out of 25mm x 25mm MS Square Tube (Medium Guage) for the Legs, 20mm x 20mm MS Square Tube for top frame, sides, foot rest supports. The Table shall be 18mm thick BWP Grade Plywood for the top, modesty frame, (front & side modesty shall be 3.00 mmm thick (5mm dia. holes) MS Perfo Sheet with SS Studs) Keyboard tray, side supports. All the visible surface shall be 1.00mm thick Laminate of Approved color & shade (Premium Grade) and other surafe shall be 0.80mm thick Laminate of approved colour & shade. The MS Leg shall be with leveller bush , Keyboard on easy sliding Telescopic slider with WireManager. All the Metal surface shall be Powder Coated as per approved colour & Shade . (The Rate shall be required with all materials, labour, transport etc.) | | | | |
| 6 | ISSUE COUNTER : (FOR UPPER GROUND FLOOR) | 4.10 | SQ.MT. | | |
| | SIZE : | | | | |
| | 3.60MTS. X 1.14MTS. X 0.76MTS. - 1 NO. | | | | |

| | | | | | |
|----|--|-------|---------|--|--|
| | Specification as per Sl. No : 1 (Issue Counter with Double Height 1.14mts. On front and 0.76mts.from inside) | | | | |
| 7 | SIDE RUNNER FOR SECTION HEAD & DM CUBICLE : (FOR FIRST FLOOR) | 1.38 | SQ.MTS. | | |
| | SIZE : | | | | |
| | 0.91MTS . X .076MTS. X 0.40MTS - 2NOS. | | | | |
| | Providing & Supplying of Side Runner for Sectio Head & DM Cubicle Table shall be made out of 18mm thick BWP Grade Plywood for the outer frame, top, shelf. front, shutters, 6mm thick Commercial Grade plywood for the back . All external surfaces & visible portion will be 1.00mm thick laminate of approved colour & shade and all inner surfaces will be 0.80mm thick laminate of approved colour & shade. Teak Wood lipping's for all base with plastic bush . The Side Runner will be provided with shutter's with Auto close Hinges with SS Handles, lock etc. | | | | |
| 8 | OPEN TYPE STORAGE UNIT (LOW HEIGHT) | 28.18 | SQ.MT. | | |
| | SIZE : | | | | |
| | FOR LIBRARY : (FOR UPPER GROUND FLOOR) | | | | |
| | 3.81MTS. X 0.91MTS. X 0.40MTS - 1 NO. | | | | |
| | 1.48MTS. X 0.91MTS. X 0.40MTS - 1NO. | | | | |
| | 2.73MTS. X 0.91MTS. X 0.40MTS. - 1NO. | | | | |
| | FOR LIBRARY LOBBY : (FOR UPPER GROUND FLOOR) | | | | |
| | 5.62MTS. X 0.91MTS. X 0.40MTS. - 1NO. | | | | |
| | 4.09MTS. X 0.90MTS. X 0.40MTS. - 1NO. | | | | |
| | 5.46MTS. X 0.91MTS. X 0.40MTS. - 1NO. | | | | |
| | FOR E LEARNING : (FOR FIRST FLOOR) | | | | |
| | 6.17MTS. X 0.91MTS. X 0.40MTS. - 1NO. | | | | |
| | 1.61MTS. X 0.90MTS. X 0.40MTS. - 1NO . | | | | |
| | Providing & Supplying of Open Type Rack made out of 18mm thick BWP Grade Plywood for the outer frame, top, shelf. and 6mm thick plywood for the back . All external surfaces & visible portion will be 1.00mm thick laminate of approved colour & shade. Teak Wood lipping's for all base with plastic bush . | | | | |
| 9 | " V " SHAPE TABLE FOR PRESENTATION ROOM (27 SEAT) : (FOR UPPER GROUND FLOOR) | 18.13 | SQ.MT. | | |
| | SIZE : | | | | |
| | 5.56MTS. X 0.76MTS. X 0.63MTS - 2NOS. | | | | |
| | 6.85MTS. X 0.76MTS. X 0.63MTS. - 1NO. | | | | |
| | 2.28MTS. X 0.76MTS. X 0.63MTS. - 1 NO. | | | | |
| | 3.60MTS. X 0.76MTS. X 0.63MTS. - 1 NO. | | | | |
| | Specification as per Sl. No : 1 | | | | |
| 10 | CENTER TABLE FOR PRESENTATION ROOM : (FOR UPPER GROUND FLOOR) | 1.91 | SQ.MT. | | |
| | SIZE : | | | | |
| | 2.10MTS. X 0.91MTS. X 0.76MTS. - 1 NO. | | | | |
| | Specification as per Sl. No : 1 (please note the modesty shall be in centre of Table) | | | | |
| 11 | BACK UNIT FOR SECTION HEAD & DM CUBICLE : (FOR FIRST FLOOR) | 3.65 | SQ.MTS. | | |
| | SIZE : | | | | |
| | 2.40MTS. X 0.76MTS. X 0.40MTS. - 2NOS. | | | | |
| | Specification as per Sl. No : 7 | | | | |
| 12 | TABLE FOR SECTION HEAD & DM CUBICLE : (FOR FIRST FLOOR) | 2.74 | SQ.MTS. | | |
| | SIZE : | | | | |
| | 1.80MTS. X 0.76MTS. X 0.76MT. - 2NOS. | | | | |

| | | | | | |
|----|---|-------|--------|--|--|
| | Providing & Supplying of Section Head & DM Cubicle Table made out of 18mm thick BWP grade Plywood for the top, front modesty and for shelf, shutter drawer front. Key Board Drawer. 12mm thick plywood for the drawer sides & back, 6mm thick plywood for the drawer base, all internal surface will be 0.8mm thick laminate of approved colour & shade & all external & visible surface will be 1.00mm thick laminate of approved colour & shade. The table top edges with 38mm thick with laminate finish. The Table will be provide with 1 no drawer and below storage unit keyboard drawer with side mounting telescopic slider, & base for CPU , wire manager, race ways for Computer cables. The Table top will be provided with 6 mm thick clear glass with all side machine grind finish. | | | | |
| 13 | E-LEARNING COUNTER : (4 SEAT SET)- 4NOS : (FOR FIRST FLOOR) | 11.07 | SQ.MT. | | |
| | SIZE : | | | | |
| | 0.75MTS. X 0.91MTS. X 0.40MTS. - 4NOS (1 SET) | | | | |
| | Providing & Supplying of 4 Seat E - Learning Table Made out of 25mm x 25mm MS Square Tube (Medium Guage) for the Legs, 20mm x 20mm MS Square Tube for top frame, sides, foot rest supports. The Table shall be 18mm thick BWP Grade Plywood for the top, top dividers . All the visible surface shall be 1.00mm thick Laminate of Approved color & shade (Premium Grade) and other surafe shall be 0.80mm thick Laminate of approved colour & shade. The MS Leg shall be with leveller bush , All the Metal surface shall be Powder Coated as per approved colour & Shade . (The Rate shall be required with all materials, labour, transport etc.) | | | | |
| 14 | SEMINAR HALL TABLE : (FOR FIRST FLOOR) | 23.91 | SQ.MT. | | |
| | SIZE : | | | | |
| | 4.36MTS. X 0.76MTS. X 0.60MTS. - 2NOS. (5 SEAT) | | | | |
| | 5.24MTS. X 0.76MTS. X 0.60MTS. - 2NOS. (6 SEAT) | | | | |
| | 6.13MTS. X 0.76MTS. X 0.60MTS. -2NOS. (7 SEAT) | | | | |
| | Specification as per Sl. No : 1 (with out Key Board Drawer's) | | | | |
| 15 | TABLE FOR LECTURE HALL : (TYPE : 1) | 30.44 | SQ.MT. | | |
| | FOR RAMANUJAM HALL : (FOR FIRST FLOOR) | | | | |
| | SIZE : | | | | |
| | " L " SHAPE : | | | | |
| | 0.90MTS. + 2.00MTS. X 0.76MTS. X 0.48MTS. - 2NOS. (4 SEAT) | | | | |
| | 1.36MTS. + 2.43MTS. X 0.76MTS. X 0.48MTS. - 2 NOS. (5 SEAT) | | | | |
| | 1.90MTS. + 2.87MTS. X 0.76MTS. X 0.48MTS. - 2NOS. (6 SEAT) | | | | |
| | 2.23MTS. + 3.31MTS. X 0.76MTS. X 0.48MTS. - 2NOS. (8 SEAT) | | | | |
| | " STRAIGHT " | | | | |
| | 1.80MTS. X 0.76MTS. X 0.48MTS. - 4NOS. (2 SEAT) | | | | |
| | Specification as per Sl. No : 1 (with out Key Board Drawer's) | | | | |
| 16 | TABLE FOR LECTURE HALL : (TYPE : 2) | 22.47 | SQ.MT. | | |
| | FOR CHANAKYA HALL : (FOR FIRST FLOOR) | | | | |
| | SIZE : | | | | |
| | 6.91MTS. X 0.76MTS. X 0.60MTS. - 1NO. | | | | |
| | 10.44MTS. X 0.76MTS. X 0.60MTS. - 1NO. | | | | |
| | 12.21MTS. X 0.76MTS. X 0.60MTS. - 1NO. | | | | |
| | Specification as per Sl. No : 1 (with out Key Board Drawer's) | | | | |
| 17 | WOODEN PARTITION WITH PARTLY 12MM THICK TOUGHENED FIXED GLASS WITH GLASS DOOR FOR SECTION HEAD & DM CUBICLE (FOR FIRST FLOOR) | 26.65 | SQ.MT. | | |
| | SIZE : | | | | |
| | 4.81MTS. X 3.40MTS. - 1NO. | | | | |
| | 4.96MTS. X 3.40MTS. - 1NO. | | | | |
| | 2.22MTS. X 3.40MTS. - 1NO. | | | | |
| | 3.36MTS. X 3.40MTS. - 1NO. | | | | |
| | LESS 12MM THICK TOUGHENED FIXED GLASS WITH GLASS DOOR | | | | |
| | SIZE : | | | | |

| | | | | | |
|----|--|----------|--------|--|--|
| | 4.81MTS. X 2.13MTS. 1NO. | | | | |
| | 4.96MTS. X 2.13MTS. - 1 NO. | | | | |
| | 2.22MTS. X 2.13MTS. - 1 NO. | | | | |
| | Providing Fabricating and Fixing Wooden Partition with partly Glass frame work consisting of 50mm x 50mm Aluminium Hollow Tube (2.00kg. per length) frame work at spacing not exceeding 600mm c/c fixed to the bottom and ceiling , the partition shall be skinned on both sides using 12mm thick BWP Grade plywood and top cover by 1.00mm thick laminate of approved colour and shade. The partition will be providing with partly 12mm thick clear Toughened glass with aluminium powder coated fish mouth cost and conveyance of all materials, labour for all items of work. (Height Approximate : 3.40mt.) (with Frosting Sticker's for Glass) (Area shall calculate for billing below ceiling height only) | | | | |
| 18 | 12MM THICK TOUGHENED FIXED GLASS WITH GLASS DOOR : | 21.92 | SQ.MT. | | |
| | SIZE : | | | | |
| | 4.81MTS. X 2.13MTS. 1NO. | | | | |
| | 4.96MTS. X 2.13MTS. - 1 NO. | | | | |
| | 2.22MTS. X 2.13MTS. - 1 NO. | | | | |
| | LESS 12MM THICK TOUGHENED GLASS DOOR : | | | | |
| | SIZE : | | | | |
| | 0.85MTS. X 2.13MTS. - 2NOS. | | | | |
| | 12MM THICK CLEAR FIXED TOUGHENED GLASS WITH DOOR WITH FROSTING STICKERS ON ALUMINIUM POWDER COATED FISH MOUTH SECTION ON TOP & BOTTOM : | | | | |
| 19 | 12MM THICK TOUGHENED GLASS DOOR : | 3.62 | SQ.MT. | | |
| | SIZE : | | | | |
| | 0.85MTS. X 2.13MTS. - 2NOS. | | | | |
| | 12MM THICK CLEAR TOUGHENED GLASS DOOR WITH FROSTING STICKERS ON PATCH FITTING. DOOR LOCK (CENTER) , HANDLES , FLOOR SPRING ETC. | | | | |
| 20 | DRAWER UNIT FOR ISSUE COUNTER | 0.84 | SQ.MT. | | |
| | SIZE : | | | | |
| | 0.46MTS. X 0.610MTS. X 0.53MTS. - 3NOS. | | | | |
| | Providing & Supplying of Drawer Unit for Issue Conuter (moveable) made out of 18mm thick BWP Plywood for top, sides, Drawer Front, 12mm thick Plywood for Drawer sides, back, 6mm thick Plywood for Drawer unit back, drawer base. All the External surface shall be 1.00mm thick laminate of apparoed colour & shade and all inner surface shall be 0.80mm thick laminate of approved colur and shade. The dawer shall ve 4 drawer's , top drawer with lock and all drawer's shallbe easy sliding teelscopic slider with handles, bush on base. | | | | |
| 21 | PLAIN CEILING | 1,110.00 | SQ.MT. | | |
| | Providing and fixing of suspended ceiling consisting of 12.50mm thick one hour fire rated gypsum plaster board suspended on GI frame work to consist of 0.9mm thick 45mm x 15mm from the soffit using properly supplied steel expansion fasteners, ceiling section (0.55mm thick) web size and flange 26mm each and 10.5mm lips fixed to the perpendicular to intermediate channel @600mm c/c using connecting clips 12.5mm thick one hour fir rated gypsum board is crew fixed to the ceiling section with 25mm dry wall screw @230mm c/c boards to be finished and jointing compound sand paper to achieve a smooth and seamless finish and 2 coats of primer suitable for plaster board applied to receive the finish all complete. | | | | |
| | GRID CEILING | 800.00 | SQ.MT. | | |

| | | | | | |
|-----------|---|--------|--------|--|--|
| | Providing & fixing of Mineral Fiber Acoustical Suspended Ceiling System in module size of 600 x 600 x 16mm with Exposed Grid . The tiles should have Humidity Resistance (RH) of 99% , NRC Light Reflective >87% Thermal Conductivity k = 0.052 - 0.057 w/mk, Colour white , Fire performance UK Class 0 / Class 1 (BS 476 pt-6 & 7) and suitable for Green Building application with Recycled content of 30%. The tile shall be laid on 24mm wide T-section flanges colour white having rotary stitching on all T SECTIONS i.e. the Main Runner, 1200mm & 600mm Cross Tees with a web height of 38mm and a load carrying capacity of 15kgs/sqm & pull out strength of minimum 100Kgs. The T Sections should have a Galvanizing of 90 grams per Sqm and need to be installed with Suspension system of approved make. Approx area. | | | | |
| | DROPS | 168.00 | SQ.MT. | | |
| | Specification as per Sl. No : 21 | | | | |
| | | | | | |
| 22 | ROLLAR BLINDS FOR WINDOW'S | 213.89 | SQ.MT. | | |
| | | | | | |
| 23 | GRAND TOTAL (EXCLUSIVE OF GST) | | | | |